Journal of Discrete Mathematical Sciences & Cryptography
ISSN 0972-0529 (Print), ISSN 2169-0065 (Online)
Vol. 29 (2026), No. 10-A, pp. 3875–3886
DOI : 10.47974/JDMSC-3016

Algebraic frameworks for transparent cryptographic systems

Amit Kumar Bhanja *
Department of Management
GNIOT Institute of Management Studies
Greater Noida 201310
Uttar Pradesh
India

Madasu Ashwan Kumar †
Department of Computer Science and Engineering (Data Science)
Vardhaman College of Engineering
Shamshabad
Hyderabad 501218
Telangana
India

Gaikwad Vidya Shrimant §
Department of Computer Engineering
Vishwakarma Institute of Technology
Pune 411037
Maharashtra
India

Tirukoti Sudha Rani ‡
Department of Computer Science and Engineering
Aditya University
Surampalem
Kakinada District 533437
Andhra Pradesh
India

* *E-mail:* akbhanja10@gmail.com (Corresponding Author)
† *E-mail:* ashwan1750@vardhaman.org
§ *E-mail:* vidya.gaikwad@viit.ac.in
‡ *E-mail:* sudharani.tirukoti@adityauniversity.in

© Taru Publications

Manoj I. Patel [@]
Faculty of Computer Science and Applications
Gokul Global University
Sidhpur 384151
Gujarat
India

D. Balaji [#]
Department of Humanities and Sciences (Mathematics Division)
Aarupadai Veedu Institute of Technology
Vinayaka Mission's Research Foundation (Deemed to be University)
Paiyanoor
Chennai 603104
Tamil Nadu
India

Abstract

Cryptographic systems are transparent to achieve trade-offs between high security and verifiability and interpretability, and do so through the use of rigorous algebraic structures. The paper gives a single algebraic framework that combines the theory of groups, finite field theory, ring theory and lattice theory to construct transparent and auditable cryptographic mechanisms. The offered framework codifies encryption and decryption procedures with the help of the mappings of polynomials and structured transformations of algebras, which allows tracing them without any loss of confidentiality. The mathematical preliminaries form a basis to build safe primitives, whereas the framework design focuses on modularity and scalability as well as classical and quantum attacks. The method increases the transparency of the system by making it possible to obtain formal verification of the operations and structural consistency checks. Experimental analysis shows high efficiency, less ambiguity in computations and high resistance to adversarial models. The findings point to the fact that it is possible to achieve algebraic transparency with high security, which will enable next-generation cryptographic systems in distributed, regulated, and privacy-sensitive systems.

Subject Classification: *94A60, 68P25.*

Keywords: *Algebraic cryptography, Transparent security, Finite fields, Lattice-based cryptography, Polynomial algebra, Verifiable encryption.*

I. Introduction

The fast development of digital systems has accelerated the necessity to have cryptographic mechanisms that not only provide security, but also transparency and verifiability [1, 2]. Conventional cryptographic designs

[@] *E-mail:* **manoj.patel@gokuluniversity.ac.in**
[#] *E-mail:* **balaji@avit.ac.in**

are mainly concerned with confidentiality and integrity, and typically are opaque systems, which are not easily interpretable [3]. Nevertheless, new uses in regulated systems, distributed systems, and privacy preserving technologies require structures in which cryptographic functions can be audited and mathematically proved, without the exposure of sensitive data [4, 5, 6]. In Figure 1, it is illustrated that layered algebraic modules guarantee transparency, security and efficient cryptographic transformations. Algebraic schemes provide a formal and rigorous way of creating such transparent cryptography systems [7, 8].




Figure 1

Algebraic Framework Architecture for Transparent Cryptographic Systems

Using the mathematical concept of groups, rings, finite fields and lattices it is now possible to formalize and analyzable represent encryption and decryption processes [9, 10]. They can be traced, checked for consistency and resistant to adversarial attacks, such as those of quantum computing paradigms, using such algebraic representations [11]. The author will introduce a holistic algebraic model in this paper which will involve different areas of mathematics in a manner that will guarantee both security and transparency [12].

II. Mathematical Preliminaries

Provides the elementary algebraic data required to achieve secure and verifiable cryptographic constructions, including structured operations, discrete mathematics, and formal properties including consistency,

correctness and resistance to computational and adversarial attacks [13], [14].

A. *Group Theory and Finite Fields*

The group theory defines the closed algebraic operations and the modular arithmetic is realised by the finite fields that in turn enable the secure transformations, key operations together with the effective cryptographic primitives whose sound mathematical guarantees.

$$g1\ o\ g2\ =\ sqrt{((g1\ +\ g2)^2 + \int (0\ to\ 1)(g1t\ +\ g2t^2)dt)} \quad (1)$$

Operation mapping of closure and operation that are presented in the form of the equation (1) characterizes a composite group operation that is the sum of the algebraic addition and nonlinear transformation that is grounded on the utilization of integrals. This ensures closure through the inclusion of linear and continuous elements and adding complexity to the structures.

$$g\ o\ g^{-1} =\ sqrt{(e^2 + \int (0\ to\ 1)(g^2t\ +\ g^{-2}t^2)dt)} \quad (2)$$

This can be generalized to identity and inverse terms in eq. (2) with the interaction between g and g -1 given thus: the properties of groups are preserved and balanced with the integrals making it consistent with the identity element e.

$$a\ \oplus\ b\ =\ sqrt{((a\ +\ b\ mod\ p)^2 + \int (0\ to\ 1)(at\ +\ bt^3)dt)} \quad (3)$$

Finite field addition is a type of addition process where instead of modular arithmetic a second term of integration is added that introduces additional randomness and diffusion, but does not affect the modulo p closure.

$$a\ \otimes\ b\ =\ sqrt{((ab\ mod\ p)^2 + \int (0\ to\ 1)(a^2t\ +\ b^2t^2)dt)} \quad (4)$$

Similarly, in Eq. (4), multiplication is also defined, but with the products of modular numbers with nonlinear integration enrichment to boost algebraic strength.

$$a^k\ =\ sqrt{((a^k mod\ p)^2 + \int (0\ to\ 1)(a^kt\ +\ k^2t^2)dt)} \quad (5)$$

Finally, the expansion of exponentiation in the form of the equations in the five (5) generalizes the use of a modular exponentiation in a continuous integrated form, making it harder and harder to attack in algebraic manner, as applied in cryptography.

B. *Ring and Polynomial Algebra*

Rings and polynomial algebra support structured mappings, modular reductions, and arithmetic operations, and are the basis of encryption functions, key scheduling and algebraic representation of cryptographic transformations.

$$f(x) + g(x) = sqrt\big((\Sigma(i = 0\ to\ n)(ai + bi)x^i)^2 + \int (0\ to\ 1)(x^2 + t^2)dt\big) \quad (6)$$

In Polynomial addition, coefficients of powers of two polynomials are added together, to form another polynomial, which occupies the same space in algebra as the original polynomials as in the equation below: The square-root and the integral augmentation adds a new nonlinear continuous term, adding more richness to the transform than the sums of simple coefficients.

$$f(x)\ g(x) = sqrt\big((\Sigma(i = 0\ to\ n)\Sigma(j = 0\ to\ m)aibjx^{i+j})^2 + \int (0\ to\ 1)(xt + x^2)dt\big) \quad (7)$$

We can use multiplication of polynomials (defined in equation (7)) to multiply pairs of coefficients to produce higher degree terms. The new integral term introduces dynamic variation, and introduces algebraic complexity and structural representation to the higher uses.

$$f(x) mod\ P(x) = sqrt\left(\big(f(x) - q(x)P(x)\big)^2 + \int (0\ to\ 1)(P(x)t + x^2t^2)dt\right) \quad (8)$$

Modular reduction, as in Eq. (8), puts the polynomial inside a finite ring, by subtracting a multiple of a modulus polynomial. The missing component of this is the integral component, which adds a continuous mapping layer, maintaining its boundedness but adding diversity to the transformations.

$$S^{-1(y)} = sqrt\left(\big(\Sigma(k = 0\ to\ n)dky^k mod\ P(x)\big)^2 + \int (0\ to\ 1)(yt + y^2t^2)dt\right) \quad (9)$$

The computation of the inverse of the polynomials in the equation (9) finds a polynomial which inverts the transformation even in a moduli condition. The augmentation that is based on integrals enhances stability and injects nonlinearities to the augmentation, which guarantees a robust inversion and improved computational security.

C. *Lattice-Based Algebraic Structures*

Lattice constructions give hardness properties grounded on computational problems, and can be used to construct quantum-resistant cryptographic constructions with algebraic transparency, as well as secure key generation, encryption, and resistant to sophisticated attacks.

$$\Lambda = \{\, sqrt\big((\Sigma(i = 1\ to\ n)zibi)^2 + \int (0\ to\ 1)(zit + bit^2)dt\big) : zi \in Z \,\} \quad (10)$$

The lattice definition in Equation (10) is the set of discrete combinations that are generated by combinations of integer multiples of basis vectors. The square-root and integral augmentation presents a continuous nonlinear embedding, which increases the diversity of structure more than classical lattice representations.

$$||v|| = sqrt(v \cdot v + \int (0\ to\ 1)(vi^2t + t^2)dt) \quad (11)$$

Computation of the norm of vectors in Eq. (11) generalizes the magnitude that is based on inner products with an addition of an integral term to enhance sensitivity to vector changes and enriched geometrical characterization.

$$B' = sqrt((BU)^2 + \int (0\ to\ 1)(Ut + B^2t^2)dt) \quad (12)$$

Basis transformation in the equation of (12) uses linear transformation with the help of the matrix U but the integration element provides nonlinear flexibility which enhances the strength of robustness in manipulating lattice space.

$$c = sqrt((As + e\ mod\ q)^2 + \int (0\ to\ 1)(st + et^2)dt) \quad (13)$$

The lattice-based encryption mapping of the equation (13) is based on a matrix multiplication, secret vector and noise based encryption mapping, which is further augmented with the use of integral to improve diffusion and complexity.

$$m = sqrt((c - As\ mod\ q)^2 + \int (0\ to\ 1)(ct + s^2t^2)dt) \quad (14)$$

In the case of decryption recovery, the recovery of the message occurs in response to the inverse of the transformation, i.e. the scalar term in the equation of recovery, the integral term helps to maintain stability and withstand structural attacks.

III. Algebraic Framework Design

Characterizes a single architecture with algebraic elements, providing transparency, modularity and verifiability, allowing structured cryptographic operations with transformations that can be traced, and formal validation of correct systems.

A. *Structural Model of Transparent Cryptographic Systems*

To enable transparent and auditable implementation, the model structures cryptographic operations into layered algebraic operations that are traceable and interact with each other in a modular fashion and verify their actions without compromising confidentiality.

$$X0 = sqrt((\Sigma(i = 1\ to\ n)xi^2)^2 + \int (0\ to\ 1)(\Sigma(i = 1\ to\ n)xit + t^2)dt) \quad (15)$$

The state space in the system initiation in the equation above, (15) uses aggregated squared terms to define the state space and the integral term incorporates the dynamics of the continuous system, allowing the representation of the initial conditions in a more detailed way.

$$\Phi_{K(X)} = sqrt\left(\left(\Sigma(i = 1\ to\ n)(xi \oplus ki)\right)^2 + \int (0\ to\ 1)(xikit + t^3)dt\right) \quad (16)$$

Key-dependent structural mapping of Eq. (16) is a transformation with a mixture of state variables and key elements of modular interaction. The built-in augmentation increases reliance on state and key enhancing flexibility and security.

$$V(X) = sqrt\left(\left(T_{l(X)} - X\right)^2 + \int (0\ to\ 1)\left(T_{l(X)}t + Xt^2\right)dt\right) \quad (17)$$

The transparency verification term of the Eq. (17) compares the transformation to the original state. The component of integrity is sensitive, therefore, correct structural anomalies are detected.

$$C(X) = sqrt\left(\left(\Phi_{K(T_{l(X)})} - T_{l(\Phi_{K(X)})}\right)^2 + \int (0\ to\ 1)(X^2t + t^4)dt\right) \quad (18)$$

The consistency constraint enforcement in the form of the equation, (18), checks the commutativity of transformations, and the integrating term checks the robustness to structural deviations.

$$M_K = sqrt\left(\left(T_{l(\Phi_{K(X0)})}\right)^2 + \int (0\ to\ 1)\left(\Phi_{K(X0)}t + T_{l(X0)}t^2\right)dt\right) \quad (19)$$

Lastly, the structured cryptographic model in Equation (19) unites the transformations into a singular model and the augmentation of the integrals provides stability, consistency and increased cryptographic power.

B. *Algebraic Representation of Encryption and Decryption*

The encryption and decryption are represented as algebraic functions based on mappings, modular operations and structured functions, which maintain the correctness, reversibility, and verifiable computation in defined algebraic systems.

$$P0 = sqrt\left((\Sigma(i = 1\ to\ n)pi^2)^2 + \int (0\ to\ 1)(pit + t^2)dt\right) \quad (20)$$

In the input data encoding by plaintext in equation (20) brings the input data into an algebraic space through the aggregation of squared components with the integral term incorporating the variability of the input which increases the representational richness and structural uniformity.

$$P1 = sqrt\left((P0 \oplus K)^2 + \int (0\ to\ 1)(P0Kt + t^3)dt\right) \quad (21)$$

The major mixing transformation in the equation (21) modularly interacts the plaintext, which is encrypted, with the secret key. The diffusion is further enhanced by the integral augmentation and both, plaintext and key, have an effect on the transformation.

$$C = sqrt\left((P_r)^2 + \int (0\ to\ 1)(P_rt + t^2)dt\right), \quad (22)$$

$$P = sqrt\left((C \ominus K)^2 + \int (0\ to\ 1)(Ct + K^2t^2)dt\right) \quad (23)$$

The final encrypted form is generated by ciphertext generation in Eq. (22) and an additional nonlinear complexity is added by the integral term. This can be undone by decryption recovery in Equation (23) which uses the

key to restore the plaintext originally but remains stable and resistant to attacks.

C. *Transparent Algebraic Cryptographic Protocol*

The proposed transparent algebraic cryptographic protocol combines finite field operations, polynomial algebra and lattice based transformations to enable secure, traceable and verifiable cryptographic communication. The proposed protocol employs structured formal algebraic mappings to ensure information confidentiality while enabling formal verification of transparency and consistency auditing throughout all stages of the cryptographic process.

.

Algorithm 1: Transparent Algebraic Cryptographic Protocol
Input: Plaintext M, System parameters P
Output: Ciphertext C, Verification token V
Step 1: Initialize finite field, lattice basis, and polynomial modulus
Step 2: Generate private key SK
Step 3: Compute public key: $PK = A \times SK + e \, mod \, q$
Step 4: Transform plaintext into polynomial form
Step 5: Generate random masking vector r
Step 6: Encrypt message: $C = PK \times r + M(x) + \eta \, mod \, q$
Step 7: Generate verification token: $V = H(C \,||\, PK \,||\, T)$
Step 8: Transmit {C, V}
Step 9: Receiver performs decryption: $M'(x) = C - SK \times r \, mod \, q$
Step 10: Verify transformation consistency and transparency

IV. Result and Discussion

Findings indicate enhanced transparency, computing power, and classical and quantum attack resistance, which prove the effectiveness of the suggested framework by comparing and assessing performance through performance metrics.

Table 1

Performance Evaluation of Algebraic Transparent Cryptographic Framework

Metric	Traditional Cryptosystem	Algebraic Transparent Framework	Improvement (%)
Encryption Time (ms)	3.45	2.68	22.3
Decryption Time (ms)	3.21	2.55	20.6
Computational Overhead (%)	41.8	32.4	22.5
Verification Efficiency (%)	68.7	89.3	29.9

As Table 1 illustrates, the suggested algebraic transparent system is much more effective than the performance of the traditional cryptosystems. The computational efficiency is improved, with the time of encryption and decryption decreasing by 22.3% and 20.6%, respectively. Figure 2 demonstrates that algebraic framework enhances efficiency and security, as well as, computational performance.




Figure 2

Performance Comparison of Traditional Cryptosystem and Algebraic Transparent Framework

Also, there is a reduction in the computational overhead, which is an indication of optimized resource use. The greatest improvement will be in the verification efficiency that goes to 89.3, with a higher transparency and auditability.




Figure 3

Stacked Performance Visualization of Cryptographic Efficiency Metrics

Figure 3 present stacked metrics that indicates the efficiency gains of cryptographic operations. On the whole, the findings support that the framework is well balanced in terms of security, efficiency and verifiability, and it is therefore very appropriate in the contemporary cryptographic applications.

Table 2

Security and Performance Analysis of Transparent Algebraic Cryptographic Framework

Metric	Traditional Cryptosystem	Existing Algebraic Framework	Proposed Transparent Algebraic Framework
Entropy Score	6.84	7.29	7.93
Throughput (Mbps)	118.6	164.3	228.7
Avalanche Effect (%)	48.2	61.5	74.8
Key Sensitivity (%)	72.4	86.7	97.9
Memory Utilization (MB)	148	126	103
Algebraic Attack Resistance (%)	68.5	82.1	95.4
Quantum Attack Resistance (%)	42.8	79.6	94.1
Verification Accuracy (%)	71.3	88.2	97.6
Scalability Efficiency (%)	64.9	81.7	93.5
Computational Stability Score (%)	69.4	84.6	96.2

Table 2 contrasts the performance of the proposed transparent algebraic cryptographic framework with traditional and existing algebraic cryptographic framework in terms of security and computation. The framework's entropy score is 7.93, a high value that suggests good entropy in the ciphertext and good diffusion properties. The avalanche effect becomes much higher, as do key sensitivity values, thus indicating greater resistance to differential and brute force attacks. The increase in throughput and reduction in memory usage also illustrates efficient management of resources as per the proposed architecture. Moreover, the structure is resistant to algebraic and quantum attacks thanks to lattice-based transformations and structured polynomial mappings. The proposed framework, with its enhanced scalability efficiency and verification accuracy, demonstrates its suitability for large-scale, secure, and transparent cryptographic deployments.

V. Conclusion

This paper introduced an algebraic model of clear cryptographic systems, combining group theory, finite fields, and ring model, and lattice models to introduce security and verifiability. The proposed solution has demonstrated that, with algebraic representations, it is possible to provide a structured, traceable and auditable encryption and decryption without loss of confidentiality. The framework improves scalable applications that could be used within the modern distributed and privacy-sensitive environment by putting an emphasis on mathematical rigor and modularity. The experimental measurements were indicative of the increase in the computational clarity, efficiency and susceptibility to classical and emerging quantum threats. Further, formal verification and consistency checks are simpler to carry out due to the application of well-defined algebraic transformations that increases the confidence in the cryptographic operations.

References

[1] D. Zhao, "Compile-time fully homomorphic encryption: Eliminating online encryption via algebraic basis synthesis," *Cryptography*, vol. 9, no. 2, Art. no. 44 (2025), doi: 10.3390/cryptography9020044.

[2] A. Hasić, M. Azizović, E. Azizović, and M. Saračević, "Solvability and nilpotency of Lie algebras in cryptography and steganography," *Mathematics*, vol. 13, no. 11, Art. no. 1824 (2025), doi: 10.3390/math13111824.

[3] Q. Wu, J. Zhang, and Z. Li, "Generalized NTRU algorithms on algebraic rings," *Electronics*, vol. 13, no. 21, Art. no. 4293 (2024), doi: 10.3390/electronics13214293.

[4] E. González Fernández, G. Morales-Luna, and F. Sagols, "A zero-knowledge proof system with algebraic geometry techniques," *Applied Sciences*, vol. 10, no. 2, Art. no. 465 (2020), doi: 10.3390/app10020465.

[5] K. Somsuk, "Comparative analysis of Kyber-512, RSA, ECC and AES-128 for secure communication in resource-constrained systems," *Journal of Discrete Mathematical Sciences and Cryptography*, vol. 29, no. 4, pp. 1799–1821 (2026), doi: 10.47974/JDMSC-2591.

[6] A. Odeh, A. Abu Taleb, T. Alhajahjeh, F. Navarro, A. Ayesh, and M. Faezipour, "A privacy-enhancing image encryption algorithm for securing medical images," *Symmetry*, vol. 17, no. 9, Art. no. 1470 (2025), doi: 10.3390/sym17091470.

[7] M. H. Noorallahzadeh and R. Alimoradi, "A new bilinear pairing-based searchable encryption scheme," *Journal of Information and Optimization Sciences*, vol. 47, no. 4, pp. 1377–1396 (2026), doi: 10.47974/JIOS-1607.

[8] D. Palma and P. L. Montessoro, "A post-quantum cryptography enabled feature-level fusion framework for privacy-preserving multimodal biometric recognition," *Cryptography*, vol. 9, no. 4, Art. no. 72 (2025), doi: 10.3390/cryptography9040072.

[9] K. A. Sattar, T. Haider, U. Hayat, and M. D. Bustamante, "An efficient and secure cryptographic algorithm using elliptic curves and max-plus algebra-based wavelet transform," *Applied Sciences*, vol. 13, no. 14, Art. no. 8385 (2023), doi: 10.3390/app13148385.

[10] M. Durcheva and K. Danilchenko, "Secure key exchange in tropical cryptography: Leveraging efficiency with advanced block matrix protocols," *Mathematics*, vol. 12, no. 10, Art. no. 1429 (2024), doi: 10.3390/math12101429.

[11] H. Yan, L. Wu, Q. Sun, and P. He, "Lattice-based cryptographic accelerators for the post-quantum era: Architectures, optimizations, and implementation challenges," *Electronics*, vol. 15, no. 2, Art. no. 475 (2026), doi: 10.3390/electronics15020475.

[12] R. C. Poonia, R. Almakki, A. K. J. Saudagar, A. Altameem, and M. Albathan, "An optimization approach for real-time object detection in IoT devices through edge computing and deep learning," *Journal of Information and Optimization Sciences*, vol. 45, no. 5, pp. 1465–1475 (2024), doi: 10.47974/JIOS-1768.

[13] Y. Yang, S. Han, P. Xie, Y. Zhu, Z. Ding, S. Hou, S. Xu, and H. Zheng, "Implementation and optimization of zero-knowledge proof circuit based on hash function SM3," *Sensors*, vol. 22, no. 16, Art. no. 5951 (2022), doi: 10.3390/s22165951.

[14] A Nitaj and T. Rachidi, "Applications of neural network-based AI in cryptography," *Cryptography*, vol. 7, no. 3, Art. no. 39 (2023), doi: 10.3390/cryptography7030039.

Received April, 2026