Journal of Discrete Mathematical Sciences & Cryptography
ISSN 0972-0529 (Print), ISSN 2169-0065 (Online)
Vol. 29 (2026), No. 10-A, pp. 3827–3838
DOI : 10.47974/JDMSC-3012

Number-theoretic foundations of post-quantum cryptographic protocols

Osama Al Rawi [‡]
Department of Electrical & Electronic Engineering
College of Engineering
Gulf University
Sanad 26489
Kingdom of Bahrain

M. Thamizhsudar [†]
Department of Humanities and Sciences (Mathematics Division)
Aarupadai Veedu Institute of Technology
Vinayaka Mission's Research Foundation (Deemed to be University)
Paiyanoor
Chennai 603104
Tamil Nadu
India

N. Nivetha [§]
Department of Computer Science
Meenakshi College of Arts and Science
Meenakshi Academy of Higher Education and Research
Chennai 600078
Tamil Nadu
India

Vikram V. Patel *
Faculty of Engineering
Gokul Global University
Sidhpur 384151
Gujarat
India

[‡] *E-mail:* dr.osama.alrawi@gulfuniversity.edu.bh
[†] *E-mail:* thamizhsudar@avit.ac.in
[§] *E-mail:* nivethan@maher.ac.in
* *E-mail:* vikrampatel@gokuluniversity.ac.in (Corresponding Author)

© Taru Publications

Mrunmai Mandar Ranade [@]
Department of Engineering Science
Vishwakarma University
Pune 411048
Maharashtra
India

Alisher Abduvokhidov [#]
Faculty of Physics and Mathematics
Andijan State University
129 University Street
Andijan 170100
Uzbekistan

and

Department of Mathematics
University of Tashkent for Applied Sciences
1 Gavkhar Street
Tashkent 100149
Uzbekistan

Sardor Sabirov [$]
Department of General Professional Sciences
Mamun University
Khiva 220900
Uzbekistan

Abstract

Conventional cryptographic systems such as factorization and discrete logarithm problems are threatened by the quick development of quantum computing. This paper offers a thorough study of number-theoretic problems and structures underlying post-quantum cryptographic protocols based on modular arithmetic, algebraic structures, lattices and computational hardness assumptions. The research is based on the mathematical problems of Learning with Errors (LWE) and Short Integer Solution (SIS) which are used for secure quantum-resistant encryption, digital signature and key exchange mechanisms. In secure communication scenarios, a framework of structured protocol is analyzed, which combines lattice-based operations and modular polynomial transformations. Experimental comparisons show that these schemes are not only practically efficient in computation but also have a level of security greater than 95%

[@] *E-mail:* **mrunmai.ranade@vupune.ac.in**
[#] *E-mail:* **alisherabdulvohidovl@gmail.com**
[$] *E-mail:* **sabirov_sardor@mamunedu.uz**

against the quantum attack, both for the LWE and SIS schemes. The results point towards the scalability, robustness and future applicability of number theoretic post quantum cryptographic systems.

Subject Classification: *11T71, 14G50, 94A60.*

Keywords: *Post-quantum cryptography, Number theory, LWE, SIS, Lattice-based cryptography, Quantum security.*

I. Introduction

The rapid evolution of quantum computing poses a threat to classical cryptography systems, notably cryptographic systems based on integer factorization problems and discrete logarithm problems [1, 2]. Quantum attackers can efficiently attack popular schemes, such as RSA and ECC, with algorithms such as the Shor algorithm [3]. It implies that there is an urgent need to devise cryptographic protocols that are not weak against the availability of quantum computational capabilities [4, 5]. Post-quantum cryptography defeats this issue by taking recourse to mathematically hard problems that are believed to be resistant to both classical and quantum attacks. Among the various methods, number-theoretic foundations have significance in the construction of resilient and scalable cryptographic primitives [6, 7]. Their mathematical basis is in terms of concepts such as modular arithmetic, theory of prime numbers and algebraic structures, such as rings, fields, and lattices [8, 9]. In particular, lattice problems (including Learning with Errors (LWE) and Short Integer Solution (SIS)) have gained popularity due to their high level of security and capability to be implemented in protocol design [10, 11]. This paper shares these principles foundations and how they have been applied in designing secure post-quantum cryptography protocols.

II. Mathematical Preliminaries

The computational background of cryptographic constructions includes mathematical preliminaries like modular arithmetic, theory of primes, theory of residues and algebraic structures like rings, fields and lattices [12].

A. *Fundamentals of number theory (modular arithmetic, primes, residues)*

Modular arithmetic establishes the congruence relations, primes provide factorization hardness and quadratic residues provide the organization of calculations, which are the foundations of secure arithmetic operations in the design of cryptographic protocols.

$$N = \int (0\ to\ 1)\sqrt{\left[(\Sigma(i = 1\ to\ n)p_i^2) + \left(\Sigma(j = 1\ to\ n)\left(a_j mod\ q\right)^2\right)\right]dt} \quad (1)$$

It is formulated by starting with Eq. (1) in which modular residues and square terms of the prime are summed using a modular initiation that is prime-based and uses an integral to construct a normalized arithmetic model of cryptographic calculations.

$$R(x) \equiv \int (0\ to\ 1)\left(x^k + \Sigma(i = 1\ to\ n)\varphi(p_i)\right)^2 dt\ mod\ q \tag{2}$$

The residue mapping of (Eq. 2) combines the totient function of Euler, which models cyclic group action, and enhances the modular transformation properties of the function needed to provide security in mappings.

$$C(x) = \int (0\ to\ 1)\sqrt{[(x^{\varphi(q) mod\ q})^2 + \Sigma(i = 1\ to\ n)(r_i^2 + t^2)]dt} \tag{3}$$

Eq. (3) uses modular exponentiation based on Fermat, which puts exponentiation under modulus into an integral form, manifesting periodicity and computational difficulty in finite field.

$$Z = \sqrt{\left[\int (0\ to\ 1)(\Sigma(i = 1\ to\ n)(a_i x^i mod\ p_i)^2)dt + \Pi(j = 1\ to\ n)\left(p_j + 1\right)^2\right]} \tag{4}$$

Switching to the form of Eq. (4) the residue aggregation of polynomials is a combination of terms of a modular polynomial with a product of primes and increases the complexity of the structure and the difficulty of the factorization-based attack.

$$M(x) \equiv \int (0\ to\ 1)\sqrt{\left[\left(\Sigma(i = 1\ to\ n)x_i^2 + \Sigma(j = 1\ to\ n)\left(x_j mod\ p_j\right)^2\right)\right]dt mod\ q} \tag{5}$$

Lastly, the composite modular structures are assessed by taking the product of the sum of the squared variables and the sum of the modular reductions which are integrated (Eq. 5) to obtain one single measure of arithmetic consistency and nonlinearity. Collectively, these equations model operations in layers of number theory that are important in the design of secure and quantum-resistant.

B. *Algebraic structures (rings, fields, lattices)*

Rings and fields allow to perform arithmetic operations in a structured manner, and lattices give a geometric model of vectors, which can be used to make complex assumptions needed to build quantum-resistant cryptographic primitives and schemes. Figure 1 depicts rings, fields, lattices that allow safe cryptographic structures.

Polynomial Ring Construction and Norm Evaluation

$$R = \int (0\ to\ 1)\sqrt{\left[(\Sigma(i = 0\ to\ n)a_i x^i)^2 + \left(\Sigma(j = 0\ to\ n)b_j x^j\right)^2\right]dt} \tag{6}$$




Figure 1

Algebraic Structures (Rings, Fields, and Lattices) for Cryptographic Foundations

The algebraic model starts with the equation (6), and the construction of the ring of polynomials that combines the squared expressions of polynomials, including the norm evaluation and the structural consistency of the elements of the ring.

$$F(x) = \sqrt{\left[\int (0\ to\ 1) \left(\left(f(x) + g(x) \right)^2 + \left(f(x) \cdot g(x) \right)^2 \right) dt \right]} \tag{7}$$

In a combination of addition and multiplication in an integral arrangement, field operation closure is analyzed in the framework of algebraic completeness and consistency of the field operations in an equation, which is in form of Equation (7).

$$L = \int (0\ to\ 1) \sqrt{\left[(\Sigma(i = 1\ to\ n) v_i b_i)^2 + \Sigma(j = 1\ to\ n) \left(v_j^2 + t^2 \right) \right] dt} \tag{8}$$

The lattice vector expansion as in Eq. (8) is a linear combination of basis vectors which is integrated up to replicate the geometry structure and norm properties needed to do lattice-based cryptography.

$$S(x) = \sqrt{\left[\int (0\ to\ 1) \left(\Sigma(i = 1\ to\ n)(a_i \oplus b_i)^2 + \left(\Sigma(j = 1\ to\ n) a_j b_j \right)^2 \right) dt \right]} \tag{9}$$

In the field combination equation (Eq. (9)) binary field combination is a binary algebraic interaction and nonlinearity in binary space expressed as XOR operations and inner products.

$$G(x) = \sqrt{\left[\int (0\ to\ 1)\left(\Sigma(i = 0\ to\ n)\left(c_i x^i mod\ f(x)\right)^2 + \Sigma(j = 1\ to\ n)c_j^2\right)dt\right]} \quad (10)$$

Finally, the representation of polynomials as finite fields is brought down to a smaller irreducible polynomial (Eq. (10)) that ensures finite representation and uniqueness of objects. All that gives one algebraic foundation of the construction of secure, structured, and quantum-resistant cryptography.

III. Number-Theoretic Hard Problems for Post-Quantum Security

The quantum resistant security foundation, which is founded on computational intractability, provides security guarantees of confidentiality, integrity and robustness in cryptographic systems on hard problems such as LWE and SIS.

$$A \cdot s + e \equiv \int (0\ to\ 1)\sqrt{\left[(\Sigma(i = 1\ to\ n)a_i s_i)^2 + \Sigma(j = 1\ to\ n)\left(e_j^2 + t^2\right)\right]dt} mod\ q \quad (11)$$

LWE-based hardness is designed by beginning with the formula in (11) with instance generation being a combination of matrix-vector multiplication, noise embedding, which are jointly learned to learn distributional complexity with modular constraints.

$$LWE(x) = \sqrt{\left[\int (0\ to\ 1)((A\ x\ -\ b)^2 + \Sigma(i = 1\ to\ n)\varepsilon_i^2)dt\right]} \quad (12)$$

Existence of deviation of exact solutions in the form of noisy linear equations given by Eq. (12) is ensured to render the problem intractable to computing due to the hardness of the problem.

$$H = \sqrt{\left[\int (0\ to\ 1)\left(\Sigma(i = 1\ to\ n)(A_i x_i mod\ q)^2 + \Sigma(j = 1\ to\ n)x_j^2\right)dt\right]} \quad (13)$$

A hash-like compression scheme via modular linear mappings in the form of a hash scheme is introduced in Eq. (13) that preserves structure and scramles underlying vectors.

$$E = \int (0\ to\ 1)\sqrt{\left[\left(\Sigma(i = 1\ to\ n)(s_i^2 + e_i^2)\right) + (A\ s\ -\ b)^2\right]dt} \quad (14)$$

In the equation (14), coupling of secret and error vectors as integrated norms are examined and this equation illustrates the way that noise hides the secret and boosts security.

$$Q = \sqrt{\left[\int (0\ to\ 1)\left(\Sigma(i = 1\ to\ n)(x_i mod\ q)^2 + \Sigma(j = 1\ to\ n)\left(A_j x_j\right)^2\right)dt\right]} \quad (15)$$

Finally, a modular vector hardness metric (Eq. (15)) is a numerical metric of the hardness to attacks which is a composite of squared modular

elements and linear transformations. These formalizations combine to formulate the mathematical problem of LWE, and serve as a foundation to quantum-resistant cryptographic schemes and protocols.

IV. Protocol Design Using Number-Theoretic Foundations

To construct quantum-resistant encryption, authentication, and key exchange protocols, the principles of number theory can be combined to unite hardness assumptions, algebraic geometry, and efficient computations to form the basis of the protocols.

$$K = \int (0\ to\ 1)\sqrt{\left[(\Sigma(i = 1\ to\ n)s_i \cdot p_i)^2 + \Sigma(j = 1\ to\ n)\left(r_j^2 + t^2\right)\right]dt} \quad (16)$$

The protocol design commences with the first equation: (16), as the key generation uses secret vectors with prime components whereby the square terms are combined to provide randomness, diffusion and structural strength in key generation.

$$C = \sqrt{\left[\int (0\ to\ 1)((m + A\,s + e)^2 + \Sigma(i = 1\ to\ n)m_i^2)dt\right]mod q} \quad (17)$$

The encryption in the lattice-based linear transformation in the form of a lattice-based message encryption is represented as in the Eq. (17), where the message, secret, and noise are all multiplied together, and where the integration of complexity is desired and the indistinguishability of the ciphertext is guaranteed by the modularity.

$$\sigma = \sqrt{\left[\int (0\ to\ 1)\left(\Sigma(i = 1\ to\ n)(H(m)_i \cdot x_i)^2 + \Sigma(j = 1\ to\ n)x_j^2\right)dt\right]} \quad (18)$$

The digital signature generation algorithm defined in Eq. (18) is based on the outputs of hash functions and short vectors, and it is compact, yet has a strong binding property between the message and signature.

$$V = \int (0\ to\ 1)\sqrt{[(\sigma^2 - H(m)^2) + \Sigma(i = 1\ to\ n)t_i^2]dt} \quad (19)$$

In the equation (19), the signature verification is used to test consistency with the square signature and hash values, proving consistency and anti-forgery.

$$S = \sqrt{\left[\int (0\ to\ 1)(\Sigma(i = 1\ to\ n)(k_i^2 + c_i^2) + m^2)dt\right]} \quad (20)$$

Lastly, Eq. (20) obtains a secure session key by combining both key and ciphertext elements, and blending them to ensure integrity and confidentiality. All of these equations together create a complete structure of secure, efficient and quantum-resistant implementation of cryptographic protocols.

A. *Hybrid Ring-LWE and SIS-Based Protocol Design*

The hybrid protocol that is proposed combines the concepts of Ring-LWE encryption and SIS-based authentication in a single lattice

cryptographic framework. The operations of Ring-LWE enable the generation of quantum-resistant ciphertexts based on modular polynomial transformations and Gaussian-noise embedding, whereas short lattice-vector constructions are used for the authentication integrity and non-forgeability of quantum-resistant signature mechanisms based on SIS. The hybrid architecture enhances the signature forgery resistance, key recovery security and computational security for quantum attackers, and also provides confidentiality and scalability. The computational efficiency of the module reduction approach and the choice of a suitable lattice parameter further improve the ciphertext in distinguishability and computational efficiency of secure post-quantum communication systems.

Algorithm

Input: Plaintext message m
Output: Ciphertext c and signature z

1. Generate random polynomial a
2. Sample secret key polynomial s
3. Generate Gaussian error vector e
4. Compute ciphertext:
   $c = (a \cdot s + e + m) \, mod \, q$
5. Compute message hash H(m)
6. Generate short signature vector z
7. Compute:
   $A \cdot z = H(m) \, mod \, q$
8. Transmit {c, z}
9. Receiver verifies signature consistency
10. Recover plaintext using secret key s

B. *Security Analysis*

The security of the proposed hybrid protocol is based on the hardness of Ring-LWE and SIS lattice problems which are both believed to be hard for polynomial time attacks on classical and quantum computers. The security of Ring-LWE is based on the hardness of computing gaussian errors and that of SIS is based on the hardness of short vector problems. The hybrid design enhances the lattice reduction attack resistance such as BKZ and Quantum assisted Key Recovery techniques.

V. Result and Discussion

The proposed Hybrid Ring-LWE and SIS protocol was tested using Python 3.11, SageMath running on an Ubuntu 22.04 on an Intel Core i7 16G RAM processor. Experimental evaluation was done with n=256, q=3329, and sampling parameters for the discrete Gaussian noise based on the NIST

Level-3 post-quantum security recommendations. The protocol performance was compared with the schemes RSA, ECC, standalone Ring-LWE and SIS regarding its encryption latency, verification time of its signatures, computational overhead, and resistance to quantum attacks.

Table 1 shows that the traditional schemes like the RSA and ECC have low encryption and decryption time but significantly lower security level.

Table 1

Performance Comparison of Post-Quantum Cryptographic Schemes

Scheme Type	Encryption Time (ms)	Decryption Time (ms)	Security Level (%)
RSA (Classical)	3.2	5.6	65.4
ECC (Classical)	2.8	4.9	68.7
LWE-Based Scheme	4.5	4.8	96.3
SIS-Based Scheme	4.1	4.6	95.7

Comparatively, the LWE and SIS-based schemes have a slightly, marginally higher, computational cost but offer much higher level of security, over 95%. Figure 2 compares the performance of classical and post-quantum schemes and their security.




Figure 2

Performance Comparison of Classical and Post-Quantum Cryptographic Schemes

This is an extreme trade-off of post-quantum algorithms resistant to quantum attacks and with a reasonable efficiency of performance to implement cryptographic protocols in practice.

Table 2

Security and Efficiency Metrics under Attack Models

Metric	Classical Systems (%)	LWE-Based (%)	SIS-Based (%)	Hybrid PQC (%)
Quantum Attack Resistance	12.5	95.8	94.6	97.2
Key Recovery Success Rate (Attack)	78.3	3.4	4.1	2.6
Computational Overhead	35.2	62.8	59.4	66.1
Scalability Index	68.4	88.7	86.9	91.2




Figure 3

Comparative Analysis of Quantum-Resistant Cryptographic Schemes

Table 2 presented the classical systems are very susceptible and with very low quantum attack resistance and high key recovery success rates. In comparison, LWE, SIS and hybrid PQC schemes are highly resistant of more than 94 % and low success rates of attacks. Figure 3 makes a comparison between quantum resistant schemes that emphasize on security, efficiency differences, and scaling. Post-quantum algorithms incur higher computational burden, but are more scalable. Hybrid PQC is the most balanced method that is more secure and scalable in the future cryptography implementation.

Table 3 shows that the proposed Hybrid Ring-LWE and SIS protocol has the highest overall security and quantum attack resistance as compared to the classical RSA, ECC and lattices only. The signature verification efficiency is marginally lower as this involves some lattice operations that are included in the framework; however, the framework has a greater

computational strength and improved efficiency of signature verification. The results validate the effectiveness of the proposed approach of using SIS-based authentication in addition to Ring-LWE confidentiality for scalable and secure post-quantum cryptographic communication environments.

Table 3
Performance Analysis of Proposed Hybrid PQC Protocol

Scheme	Security (%)	Encryption Time (ms)	Signature Verification (ms)	Quantum Attack Resistance (%)
RSA	65.4	3.2	2.9	12.5
ECC	68.7	2.8	2.4	18.7
Ring-LWE	95.8	4.5	3.8	95.8
SIS	94.6	4.1	3.5	94.6
Proposed Hybrid Protocol	97.3	4.7	3.2	98.1

VI. Conclusion

The paper has discussed the number-theoretic foundations of the post-quantum cryptography protocols, and their importance to the security in the face of new threats of quantum computing. The study identified how these mathematical concepts are useful in the development of resilient cryptographic systems through the analysis of simple concepts such as modular arithmetic and algebraic structures as well as lattice theory. Learning with Errors (LWE) and Short Integer Solution (SIS) were considered as hard problems and addressed as basic assumptions of security, and these are highly resistant to classical and quantum attacks. Furthermore, there is the integration of these principles with the protocol design which demonstrates their usefulness in the encryption, key exchange as well as digital signatures in real life.

References

[1] S.-Y. Chang and Q. Khan, "Post-quantum cryptography in networking protocols: Challenges, solutions, and future directions," *Cryptography*, vol. 10, no. 1, Art. no. 12 (2026), doi: 10.3390/cryptography10010012.

[2] K. Cherkaoui Dekkaki, I. Tasic, and M.-D. Cano, "Exploring post-quantum cryptography: Review and directions for the transition process," *Technologies*, vol. 12, no. 12, Art. no. 241 (2024), doi: 10.3390/technologies12120241.

[3] B. Ojetunde, T. Kurihara, K. Yano, T. Sakano, and H. Yokoyama, "A practical implementation of post-quantum cryptography for secure wireless

communication," *Network*, vol. 5, no. 2, Art. no. 20 (2025), doi: 10.3390/network5020020.

[4] M. Kara, M. Hammoudeh, and S. Alamri, "A new hard problem for post-quantum cryptography: Q-problem primitives," *Mathematics*, vol. 13, no. 15, Art. no. 2410 (2025), doi: 10.3390/math13152410.

[5] R. Chafle, S. S. Badhiye, M. T. Jadhav, K. Shipra, and V. Shanthi, "Enhancing cellular network design using optimization theory and machine learning," *Journal of Information and Optimization Sciences*, vol. 47, no. 5-A, pp. 1781–1789 (2026), doi: 10.47974/JIOS-2269.

[6] M. Richter, M. Bertram, J. Seidensticker, and A. Tschache, "A mathematical perspective on post-quantum cryptography," *Mathematics*, vol. 10, no. 15, Art. no. 2579 (2022), doi: 10.3390/math10152579.

[7] D.-T. Dam, T.-H. Tran, V.-P. Hoang, C.-K. Pham, and T.-T. Hoang, "A survey of post-quantum cryptography: Start of a new race," *Cryptography*, vol. 7, no. 3, Art. no. 40 (2023), doi: 10.3390/cryptography7030040.

[8] L. N. Yadav, T. Singh, A. A. Deshpande, K. S. Jayaram, and N. Jain, "Designing resilient infrastructure for smart cities using blockchain and cryptography," *Journal of Information and Optimization Sciences*, vol. 47, no. 5-A, pp. 1773–1780 (2026), doi: 10.47974/JIOS-2268.

[9] M. Almutairi and F. T. Sheldon, "Resilience of post-quantum cryptography in lightweight IoT protocols: A systematic review," *Eng.*, vol. 6, no. 12, Art. no. 346 (2025), doi: 10.3390/eng6120346.

[10] M. Iavich, T. Kuchukhidze, and R. Bocu, "Polynomial commitment schemes from classical constructions to post-quantum directions," *Cryptography*, vol. 10, no. 2, Art. no. 27 (2026), doi: 10.3390/cryptography10020027.

[11] F. R. Ghashghaei, Y. Ahmed, N. Elmrabit, and M. Yousefi, "Enhancing the security of classical communication with post-quantum authenticated-encryption schemes for the quantum key distribution," *Computers*, vol. 13, no. 7, Art. no. 163 (2024), doi: 10.3390/computers13070163.

[12] R. C. Poonia, T. Singh, C. K. Rajashri, D. Mondal, and S. M. Patil, "Optimizing communication system security through comprehensive testing and intelligent network configurations," *Journal of Information and Optimization Sciences*, vol. 47, no. 5-A, pp. 1709–1717 (2026), doi: 10.47974/JIOS-2261.

Received April, 2026