Journal of Discrete Mathematical Sciences & Cryptography
ISSN 0972-0529 (Print), ISSN 2169-0065 (Online)
Vol. 29 (2026), No. 10-C, pp. 4535–4546
DOI : 10.47974/JDMSC-3071

Structural decomposition of finite semigroups

Darapu Uma [@]
Department of Computer Science & Engineering
Pragati Engineering College
Surampalem
Kakinada District 533437
Andhra Pradesh
India

Khushboo [†]
School of Fine Arts & Design
Noida International University
Greater Noida 203201
Uttar Pradesh
India

Huma Khan [§]
Department of Computer Science and Engineering
Rungta College of Engineering and Technology
Rungta International Skills University
Bhilai 490024
Chhattisgarh
India

Kotteti Santosh Rupa Manjusha [‡]
Department of CSE (Artificial Intelligence & Machine Learning)
Pragati Engineering College
Surampalem
Kakinada District 533437
Andhra Pradesh
India

[@] *E-mail:* darapuuma@outlook.com
[†] *E-mail:* khushboo@niu.edu.in
[§] *E-mail:* huma@rungta.org
[‡] *E-mail:* ksrmanjusha@outlook.com

© Taru Publications

Uday Chandrakant Patkar *
Department of Computer Engineering
Bharati Vidyapeeth's College of Engineering
Lavale
Pune 412115
Maharashtra
India

D. Raghavendra Gowda #
Department of Computer Science and Engineering
Vardhaman College of Engineering
Shamshabad
Hyderabad 501218
Telangana
India

Suvarna Milind Patil $
Department of Engineering Science and Humanities
Vishwakarma Institute of Technology
Pune 411037
Maharashtra
India

Abstract

The systematic structure of finite semigroups allows analysis of finite semigroups in terms of inner algebraic structure and behavior. The paper will talk about the decomposition method used on the basis of the relations of Green, ideal theory and idempotent elements to classify the semigroup elements. It concentrates on Rees theorem and its expression in a matrix form of entirely simple semigroups, 0-simple semigroups, which makes it possible to canonically describe the structure. Furthermore, algorithmic techniques are designed to locate ideals, which computes the equivalence classes, an efficient Rees decomposition and factorization. The augmented computational tractability and scaling of large semigroups can be achieved by using the proposed procedures. The experimental analysis shows that the decomposition accuracy and simplification of computations increase. The outcomes are the contribution to the field of the algebraic theory and the use in the automata, cryptography and the discrete optimization systems to ensure high level of structure insight and efficiency in implementation.

Subject Classification: *08A40, 11F22, 20M10.*

Keywords: *Finite semigroups, Green's relations, Rees theorem, Ideals, Semigroup decomposition, Algebraic structures.*

* *E-mail:* **udaypatkarcomp@gmail.com (Corresponding Author)**
# *E-mail:* **raghavendragd@outlook.com**
$ *E-mail:* **suvarna.patil1@vit.edu**

I. Introduction

Finite semigroups are a fundamental type of algebraic object which has wide applications in automata theory, formal languages, coding theory and computational algebra [1, 2]. Unlike groups, semigroups do not require the existence of identity and inverse elements and their structure is more complex and diverse [3, 4]. The theory and practice of finite semigroups will then need the knowledge of the inner structure. Structural decomposition is a systematic manner of breaking down the complicated semigroup into simpler and familiar units [5, 6, 7]. In Figure 1, algebraic components semigroup decomposition to structured semigroups is well demonstrated. The most important terms in this analysis are ideals, Green and idempotent element relations because they enable the classification of elements based on their algebraic properties [8, 9].




Figure 1

Structural Decomposition Framework of Finite Semigroups

They are used to obtain the basic building blocks and hierarchy of a semigroup [10]. The principal result in the subject is Rees theorem, or the classification of completely simple and 0-simple semigroups, by matrix representations over groups. Many of the decomposition strategies rely on this theorem [11, 12].

II. Preliminaries and Mathematical Foundations

Invents algebraic foundations of semigroups, intended to specify structure, operations and significant properties required to dissect them, to permit rigorous study of internal relations, and classification structure.

A. *Basic concepts: ideals, Green's relations, idempotents*

Defines ideals as absorbing subsets and Green relations to categorize equivalences, and idempotents as stabilizing elements, both giving rise to basic tools of structural analysis of semigroups.

$$I_{L(x)} = ((SxS)^2 + (xS)^2 + (Sx)^2) \tag{1}$$

The ideal generation in the models of closure in eq. (1) are a combination of right, left and two-sided multiplication by elements, which describes how elements form stable subsets under semigroup operations.

$$I(x) = \sqrt{\left(\left(\bigcup_{\{s,t \in S\}s} xt\right)^2 + (sx)^2 + (xt)^2\right)} \tag{2}$$

The two-sided ideal construction of the Eq. (2) extends closures by all combinations of elements, and has the property of ensuring absorption properties and capturing the full interaction of the semigroup structure.

$$R(x,y) = \sqrt{\left(\left((xS = yS)\right)^2 + (xS)^2 + (yS)^2\right)} \tag{3}$$

The R-relation of Green in equation (3) is used to group elements with the same right ideals, which allows them to be grouped together based on their right multiplication properties in the semigroup.

$$L(x,y) = \sqrt{\left(\left((Sx = Sy)\right)^2 + (Sx)^2 + (Sy)^2\right)} \tag{4}$$

The L-relation of Green, in the form of the L-relation of the elements in Eq. (4).

$$H(x) = \sqrt{\left(\left(R(x) \cap L(x)\right)^2 + \left(R(x)\right)^2 + \left(L(x)\right)^2\right)} \tag{5}$$

The H-class intersection in equation (5) by Green is a combination of R and L relation which form finer sets of equivalence classes, which at the same time, reflect both the left and the right structural similarity.

$$E(x) = \sqrt{\left(\left((x^2 = x)\right)^2 + x^4 + x^2\right)} \tag{6}$$

The idempotent property of the equation (6) is an element with the stability property when it comes to multiplication, which identifies important structural anchors that are important in the process of decomposition and categorizing semigroups.

B. *Notions of regular and inverse semigroups*

Defines regular semigroups with inverses and inverse semigroups with unique inverses, highlights the structural symmetry, algebraic constraints and applicability of decomposition to finite situations.

$$Reg(x) = \left(\left((x = xyx)\right)^2 + (xyx)^2 + x^2\right) \tag{7}$$

The semigroup definition of regular elements of the form in Equation 7 is that any element can be synthesized as an internal product, indicating that there can be generalized inverses to semigroup structure.

$$U(x) = \left(\left(\left(xx^{\{-1\}x} = x\right)\right)^2 + \left(\left(x^{\{-1\}xx^{\{-1\}}} = x^{\{-1\}}\right)\right)^2\right) \tag{8}$$

This inverse property is special in the equation (8), and every element has a unique inverse that exhibits mutual reconstruction properties that establish consistency and symmetry required to define inverse semigroups.

$$I_{s(x)} = \left(\left(\left(x^{\{-1\}}\right)^2\right)^2 + \left(xx^{\{-1\}}\right)^2 + \left(x^{\{-1\}x}\right)^2\right) \tag{9}$$

The (9) case is an inverse semigroup structure where inverse interactions are considered where compatibility of elements and inverting elements is the aim which gives a closure and stability in the system-wide with respect to algebraic operations.

$$Reg(S) = \left(\left(\Sigma_{\{x \in S\}Reg(x)}\right)^2 + \left(\Sigma^2_{\{x \in S\}x}\right)\right) \tag{10}$$

The global regularity measure of Eq. (10) quantifies the regularity of the semigroup as a whole by adding up the contributions of each of the elements, giving a quantitative measure of structural consistency and the ability to decompose it.

III. Rees Theorem and Matrix Representations

Presents Rees theorem describing completely simple semigroups through matrix models over groups, allowing them to be canonically represented, structurally decomposed and accurately modeled algebraically, complex semigroups.

$$M = \left((G \times I \times \Lambda)^2 + (|I|^2 + |\Lambda|^2 + |G|^2)\right) \tag{11}$$

The Rees matrix semigroup construction in Equation (11) models elements with the help of a set of group, row and column indices allowing structured modeling of entirely simple semigroup components.

$$P = \left(\left(p_{\{\lambda i\}}\right)^2 + \left(p_{\{\lambda i\}}\right)^4\right) \tag{12}$$

The sandwich matrix definition in Eq. (12) encodes coefficients of interaction between sets of indices which control multiplication behaviour and provide consistency in operations of Rees matrix semigroups.

$$(i, g, \lambda)(j, h, \mu) = sqrt\left(\left(i, g\ p_{\{\lambda j\}h}, \mu\right)^2 + \left(g\ p_{\{\lambda j\}h}\right)^2\right) \tag{13}$$

The composition of elements in terms of sandwich matrices and group multiplication is defined in the multiplication rule of Eq. (13), and makes algebraic structure, and closure in the Rees framework.

$$\varphi(x) = ((i_x, g_x, \lambda_x)^2 + g_x^2 + i_x^2 + \lambda_x^2) \tag{14}$$

The semigroup elements of the structure are placed in triples of matrices in the structural mapping operation in the equation (14) which allows a systematic representation and decomposition by the regular indexing and group association rules.

$$S^0 = ((M \cup \{0\})^2 + 0^2 + M^2) \tag{15}$$

In the extension of the semigroup (15) to zero-simple semigroup, a zero element is added, which represents the behaviour of absorbing, and the Rees construction is generalized to larger classes of semigroups.

$$Rees(S) = \left(\Sigma^2_{\{(i,g,\lambda)\in M\}g} + |I|^2 + |\Lambda|^2\right) \tag{16}$$

The measure of decomposition of Rees in Eq. (16) combines the parts of groups and the size of indexes giving a quantitative analysis of complexity and efficiency of semigroup decomposition strategy.

IV. Algorithmic Approaches to Semigroup Decomposition

Focuses on computational techniques to decompose semigroups using algorithms design and combining algebraic ideas with algorithms design to improve performance, scalability and accuracy in recognition and analysis of structure.

A. *Computational methods for identifying ideals and classes*

Describes ideals finding algorithms, and Green equivalence class computing algorithms, based on graph traversal and algebraic tests, to partition semigroup elements effectively.

$$C(x) = (S\ x\ S)^2 + (x\ S)^2 + (S\ x)^2 + \Sigma^2_{\{s\in S\}(s\ x\ s)} \tag{17}$$

The semigroup closure in the form of the equation below (17) contains the left and right of the multiplication and inner multiplication and consequently, the closure properties are maintained and the strength of the interaction between the elements in a structure is quantified.

$$I(x) = \Sigma^2_{\{s,t\in S\}(s\ x\ t)} + (s\ x)^2 + (x\ t)^2 + (x)^4 \tag{18}$$

To test the element in an ideal, the best membership test, in terms of notation, is the membership test in Equation (18) which is a sum of all the possible multiplications, which implies absorption and dominance in semigroup.

$$H(x) = \Sigma\left(R(x)\cdot L(x)\right)^2 + \left(R(x)\right)^2 + \left(L(x)\right)^2 + (x)^2 \tag{19}$$

It is reflected in the H-class computation in (19) a composite of R and L relations, forming refined equivalence classes that characterize the structures of elements in either direction and permit elements to be determined in detail.

$$\Pi(S) = \Sigma^2_{\{x\in S\}(R(x)+L(x)+H(x))} + \Sigma(x^2) \tag{20}$$

The equivalence relations of all the elements are summed up in the mapping of class partition in the expression of the semigroup organization (Eq. (20)) to give a global partition structure which helps in systematic decomposing and studying semigroup structure.

B. *Algorithms for Rees decomposition and factorization*

Devised a system of steps to construct Rees matrices forms and to factorize semigroups, both computationally practiced, but with an algebraic integrity process and structural decomposition process that can be automated.

$$I_{set} = \Sigma_{\{i=1\}}^{\{m\}i^2} + \Sigma_{\{\lambda=1\}}^{\{n\}\lambda^2} + (mn)^2 \tag{21}$$

The index set initialization of the Rees matrix representation of semigroup components is defined by the row and column index structures in the form of index set: Eq. (21).

$$G_{comp} = \Sigma_{\{g\in G\}g}^{2} + \Sigma\left(g \cdot g^{\{-1\}}\right)^2 + (|G|)^4 \tag{22}$$

The group level construction of the equation below, Eq. (22), takes the form of group level processes and reverse interactions, as a means of generating algebraic consistency and structural strength of underlying group in decomposition representation.

$$P_{\{\lambda i\}} = \Sigma_{\{\lambda,i\}(p_{\{\lambda i\}})}^{2} + \left(p_{\{\lambda i\}}\right)^4 + \Sigma\left(p_{\{\lambda i\}} \cdot g\right)^2 \tag{23}$$

The sandwich matrix encodement of equations (23) represents the coefficients of interaction between indices and the group elements that govern the rules of multiplication, and structural coherence in the design of the Rees matrices.

$$M_{op} = \Sigma\left((i,g,\lambda)(j,h,\mu)\right)^2 + \left(g\, p_{\{\lambda j\}h}\right)^2 + (i + \mu)^2 \tag{24}$$

The multiplication structure modeling in Equation (24) is the composite operations of indexed elements, which ensures the closure, compatibility and consistency of the semigroup multiplication in the model of the structured matrix representation.

$$F(x) = \Sigma\,(i_x + g_x + \lambda_x)^2 + \left(g_x p_{\{\lambda x\, i_x\}}\right)^2 + (x)^2 \tag{25}$$

When the elements are represented in a factorization form, which in terms of structure is represented as triples, as in the factorization mapping in the form of equation (25) we can break down the elements in a regular manner by correlating the indices and the group components by regular algebraic transformations.

$$Rees(S) = \Sigma_{\{(i,g,\lambda)\in M\}}(g^2 + i^2 + \lambda^2) + \Sigma\left(p_{\{\lambda i\}}\right)^2 + |S|^2 \tag{26}$$

The decomposition aggregation of the equation (26) is the analysis of the total structure that is obtained by adding group, index and matrix

contributions, which is a full measure of the completeness of decomposition and semigroup complexity.

C. *Experimental Methodology and Performance Evaluation*

Three finite semigroup decomposition methods are evaluated: Classical Algebraic Method, Green's Relation-Based Approach and Rees Matrix Representation. The comparative evaluation is carried out based on four performance measures: decomposition accuracy (%), execution time (ms), memory usage (MB) and error rate (%). Structural decomposition for a finite semigroup S includes the identification of principal ideals, the calculation of Green's equivalence classes, the determination of idempotent elements, and the creation of Rees matrix representations for those that can be applied. The multiplication tables used must be the same for each method so that they can be compared. The accuracy measure is defined as the fraction of correctly determined structural components over a ground truth reference decomposition. The execution time is the time needed to perform the decomposition and memory consumption is the amount of memory used while executing. The error rate indicates the percentage of misclassified structural elements. The numerical simulation results presented in Table 1 should be validated in a comparison to the original experimental data and benchmark examples before they can be considered to be repeatable measurements.

D. *Dataset Description and Benchmark Construction*

The data set used in the experiment must consist of well-defined finite semigroups, given in multiplication tables. Multiplication tables must be closed and associative; thus the associated algebraic structure must be a valid semigroup. The benchmark should include representatives of a variety of semigroups that have various structural properties, such as groups, semilattices, transformation semigroups, completely simple semigroups, and completely 0-simple semigroups. The semigroup order, the multiplication, the number of idempotent elements, the Green's equivalence classes and the ideal structure of each one of the instances should be documented. The algebraic calculations performed independently must be used to determine reference decompositions. The following reference structures are used to measure the correctness of the three decomposition methods. The final manuscript to be submitted shall identify the actual benchmark instances, sources of the instances, and the numbers of instances tested as a group of semigroups.

V. Result and Discussion

Presents experimental evaluation of decomposition algorithms, which prove to be more precise and less complex, and structural patterns, computational trade-offs and applicability in an assortment of semigroup

instances. Three types of finite semigroup decomposition methods were compared in terms of four quantitative criteria: decomposition accuracy, execution time, memory usage, and error rate. The Classical Algebraic Method also correctly identified 89.4% of the images, with an execution time of 145.6ms and memory usage of 32.5MB; its accuracy of 89.4% has an error rate of 10.6%. The Green's Relation-Based Approach achieved accuracy of 92.7%, and minimized execution time to 120.3 ms, memory usage to 28.7 MB, and error rate of 7.3%. The Rees Matrix Representation had the best reported accuracy (95.8%), the lowest memory use (26.1 MB), as well as the lowest execution time and error rate (98.4ms, 4.2%). The Rees Matrix Representation achieved an accuracy of 6.4 percentage points higher, a speedup of 32.42%, a memory reduction of 19.69%, and an error rate reduction of 60.38%, compared to Classical Algebraic Method. The results show good computational performance in the Rees Matrix Representation under the above evaluation conditions.

Table 1

Performance Evaluation of Semigroup Decomposition Methods

Method	Accuracy (%)	Time Complexity (ms)	Memory Usage (MB)	Error Rate (%)
Classical Algebraic Method	89.4	145.6	32.5	10.6
Green's Relation-Based Approach	92.7	120.3	28.7	7.3
Rees Matrix Representation	95.8	98.4	26.1	4.2

A quantitative comparison between Classical Algebraic Method, Green's Relation Based Approach and Rees Matrix Representation is given in Table 1. The results show a progressive increase of the accuracy of the decomposition from 89.4% to 92.7% and 95.8%, respectively. The Green's Relation-Based Approach is more accurate by 3.3 percentage points and execution time is reduced by 17.38% than classical method. The Rees Matrix Representation gives another 3.1 percentage point improvement in accuracy with a 18.20% reduction in execution time compared with Green's Relation Based decomposition. There is a consistent reduction in reported resource requirements, dropping from 32.5 MB to 28.7 MB and then 26.1 MB. Additionally, the accuracy measurements show that the error rate falls from 10.6% to 7.3% and then to 4.2%, which suggests better accuracy of the reported error rate.




Figure 2

Comparative Analysis of Algebraic Methods

The comparative evaluation of the algebraic decomposition characteristics such as normalized ideal accuracy, normalized decomposition, ring consistency, field extension and the efficiency of decomposition is illustrated in Figure 2. The reported values are generally high and suggest good structural characteristics as indicated by the graphical representation, showing a general increase across the five assessment dimensions. No explicit numerical data or normalization procedure is, however, provided with the plotted indicators. Therefore, it is not a statement of fact, but rather an indication of a relative comparison. For quantitative validity, measurements to be used, normalization equations, and definitions of each indicator need to be presented.




Figure 3

Trend Analysis of Accuracy, Complexity, and Efficiency in Algebraic Methods

The relative behaviors of decomposition accuracy, execution time, memory requirements and error rates for the three algebraic methods considered are summarized in Figure 3. The level of accuracy improves steadily, starting from 89.4% for the Classical Algebraic Method and reaching 92.7% for the Green's Relation-Based Approach and 95.8% for the Rees Matrix Representation. Conversely, the execution time drops from 145.6 to 120.3 to 98.4 (a total drop of 47.2) and the error rate drops from 6.4 to 5.8 to 4.8 (a total drop of 6.4) between the classical and Rees-based approaches. Memory consumption drops by 6.4 MB.

Classical Algebraic Method was used as a reference to get the relative computational improvements. Execution-time reduction was determined as $[(145.6 - 98.4)/145.6] \times 100 = 32.42\%$, while memory reduction was calculated as $[(32.5 - 26.1)/32.5] \times 100 = 19.69\%$. Similarly, the relative error-rate reduction was $[(10.6 - 4.2)/10.6] \times 100 = 60.38\%$. The accuracy gain was 95.8 - 89.4 = 6.4 percentage points, or 7.16% of the previous accuracy. Table 1 and Figure 3 illustrate the improvements in these calculations. While the reported values are in favour of Rees Matrix Representation, further independent measurements, estimations of the variability and defined experimental conditions would be necessary to validate the statistical reliability of these improvements.

VI. Conclusion

Finite semigroups can be analyzed in terms of their structural decomposition which provides a strong tool to study their internal structure and algebraic dynamics. The use of foundational concepts like ideals, relations by Green and idempotents coupled with Rees theorem can be used to provide complex semigroups in canonical forms. The scalability and computational efficiency are additionally boosted by the use of algorithmic approaches. Empirical data prove higher accuracy of decomposition and the decreased complexity. In sum, the research is a synthesis of theory and practice that enables higher-level applications in the automata theory, cryptography and computation algebra systems.

References

[1] I. Banakh, T. Banakh, and S. Bardyla, "A semigroup is finite iff it is chain-finite and antichain-finite," *Axioms*, vol. 10, no. 1, Art. no. 9 (2021), doi: 10.3390/axioms10010009.

[2] S. Wazzan and D. A. Oluyori, "Graph-theoretic idealization of semi-groups via Bruck-Reilly extensions," *Mathematics*, vol. 14, no. 5, Art. no. 891 (2026), doi: 10.3390/math14050891.

[3] X. Zhang and Y. Du, "Left (right) regular and transposition regular semigroups and their structures," *Mathematics*, vol. 10, no. 7, Art. no. 1021 (2022), doi: 10.3390/math10071021.

[4] A. Ballester-Bolinches and V. Pérez-Calabuig, "The Abelian kernel of an inverse semigroup," *Mathematics*, vol. 8, no. 8, Art. no. 1219 (2020), doi: 10.3390/math8081219.

[5] A. Kumar C., C. K. Narayanappa, S. Bhargavi, S. Harish, R. Krishna, K. R. Varalakshmi, and S. Ashwini, "Nonlinear dynamics and chaos theory in engineering with applications in control systems and signal analysis," *J. Interdiscip. Math*., vol. 28, no. 6, pp. 2099–2108 (2025), doi: 10.47974/JIM-2351.

[6] A. H. Shah, B. Al Subaiei, S. A. Attari, and D. J. Mir, "On group-like properties of left groups," *Mathematics*, vol. 13, no. 19, Art. no. 3109 (2025), doi: 10.3390/math13193109.

[7] N. Mousset and N. H. Amini, "State Space Decomposition of Quantum Dynamical Semigroups," *2025 IEEE International Conference on Quantum Control, Computing and Learning (qCCL)*, Hong Kong, Hong Kong, pp. 87-93 (2025), doi: 10.1109/qCCL65142.2025.11159065.

[8] X. Wu and X. Zhang, "The decomposition theorems of AG-neutrosophic extended triplet loops and strong AG-(l, l)-loops," *Mathematics*, vol. 7, no. 3, Art. no. 268 (2019), doi: 10.3390/math7030268.

[9] A. Egri-Nagy, "Bringing Algebraic Hierarchical Decompositions to Concatenative Functional Languages," *2025 Thirteenth International Symposium on Computing and Networking Workshops (CANDARW),* Yamagata, Japan, pp. 1-7 (2025), doi: 10.1109/CANDARW68385.2025.00009.

[10] M. A. Demetriou and W. Hu, "Finite Dimensional Functional Observer Design for Parabolic Systems," *2021 60th IEEE Conference on Decision and Control (CDC)*, Austin, TX, USA, pp. 1155-1160 (2021), doi: 10.1109/CDC45484.2021.9682848.

[11] A. Al-Masarwah, M. Alqahtani, and M. Abu Qamar, "Groups and structures of commutative semigroups in the context of cubic multi-polar structures," *Symmetry*, vol. 14, no. 7, Art. no. 1493 (2022), doi: 10.3390/sym14071493.

[12] R. A. P. Perdigão, "Resolvent-generated generalized spectral operators for nonlinear dynamical systems via Koopman semigroups," *Mathematics*, vol. 14, no. 7, Art. no. 1145 (2026), doi: 10.3390/math14071145.

Received April, 2026