

Exploring advanced data security challenges and solutions in intelligent network substation

Anindita Khade *

*Department of Computer Engineering
School of Technology Management and Engineering
SVKM'S NMIMS (Deemed to be University)
Navi Mumbai 410210
Maharashtra
India*

Anand B. Deshmukh [†]

*Department of Information Technology
Sipna College of Engineering and Technology
Amravati 444701
Maharashtra
India*

Gayatri Mirajkar [§]

*Department of Electronics and Telecommunication Engineering
Arvind Gavali College of Engineering
Satara 415015
Maharashtra
India*

Ganesh Jorvekar [‡]

*Department of Computer Technology
Sanjivani K.B.P. Polytechnic
Kopargaon 423603
Maharashtra
India*

* E-mail: aninditaac1987@gmail.com (Corresponding Author)

[†] E-mail: abdeshmukh@sipnaengg.ac.in

[§] E-mail: gayatrimirajkar@gmail.com;
gayatri.mirajkar@agce.edu.in

[‡] E-mail: ganesh.jorvekar@gmail.com

Prolay Ghosh [®]

*Department of Information Technology
JIS College of Engineering
Kalyani
Nadia 741235
West Bengal
India*

Sarvar Iskandarov Baltabaevich [#]

*Department of Mathematical Analyze
Urgench State University
Urgench City 220100
Uzbekistan*

Abstract

Modern smart grids are held together by intelligent network substations that allow data to be sent and received in real time, tracking to be done from afar, and decisions to be made automatically. But as they get more complicated, they become more vulnerable to advanced cyber risks like data manipulation, denial-of-service attacks, and attacks from inside the company. This essay talks about some of the hardest things about keeping private operational data safe, focussing on flaws in communication methods, Internet of Things (IoT) devices, and cloud-based control systems. We look at advanced options like blockchain for keeping data safe, homomorphic encryption for safe computing, AI-powered intrusion detection, and zero-trust frameworks. The suggested methods show how next-generation substations can have resilience, dependability, and privacy protected by integrated security designs.

Subject Classification: 68M10.

Keywords: Intelligent substation, Data security, Cybersecurity challenges, Blockchain, Homomorphic encryption.

I. Introduction

The fast development of smart grids has changed how energy is distributed and monitored. Intelligent network substations are the most important parts of this infrastructure [1, 2]. These substations allow for real-time data collection, automated decision-making, and remote control [3]. This creates a dynamic environment that makes modern power systems more efficient, reliable, and scalable. However, these systems are becoming more vulnerable to advanced cyber dangers because they are becoming more complicated and linked to each other [4, 5]. Bad people take advantage of flaws in communication protocols,

[®] E-mail: prolay.ghosh@jiscollege.ac.in

[#] E-mail: sarvar.i@urdu.uz

IoT devices, and cloud-based control systems. This can cause major operations to stop, private data to be changed, and large-scale denial-of-service attacks [6, 7]. So, one of the most important challenges for the future of smart grids is to make sure that operating data in intelligent substations is kept private, correct, and accessible. [8] Using traditional security methods isn't always enough to protect against complex attack routes, so more advanced solutions need to be added. New ideas like blockchain for unchangeable data transfer, homomorphic encryption for safe computing [9, 10, 11].

II. Proposed Security Solutions

A. Homomorphic encryption for privacy-preserving computation

Homomorphic encryption lets us do safe calculations on protected data, keeping it private and letting operators do useful analysis without giving out private operating information [12]. Figure 1 shows the homomorphic encryption workflow.




Figure 1
Homomorphic Encryption Workflow for Privacy-Preserving Computation

Plaintext input: $m \in \mathbb{Z}_n$

Choose encryption key pair: (pk, sk)

Encryption:

$$c = E_{pk}(m) = g^m \cdot r^n \bmod n^2 \quad (1)$$

Random factor: $r \in \mathbb{Z}_n^*$

Define homomorphic addition:

$$E(m1) \cdot E(m2) = E(m1 + m2) \quad (2)$$

Define homomorphic multiplication by scalar:

$$E(m)^k = E(km) \quad (3)$$

Secure sum across devices:

$$C = \prod_{i=1}^N E(mi) \quad (4)$$

Result ciphertext:

$$C = E(\sum_{i=1}^N mi) \quad (4)$$

Decryption:

$$m = D_{sk(c)} = \frac{(L(c^\lambda \bmod n^2))}{(L(g^\lambda \bmod n^2))} \bmod n \quad (6)$$

$$\text{Function } L(u) = \frac{(u-1)}{n} \quad (7)$$

Computation on encrypted data ensures no raw data exposure

Privacy score is proportional to entropy $H(C)$

Final secure output:

$$y = f(D_{sk(c)})$$

B. AI-driven intrusion detection and anomaly recognition

AI-powered breach detection uses machine learning to spot oddities, catch hacks as they change over time, and make systems more resistant to advanced chronic threats [13].

Input features:

$$X = \{x_1, x_2, \dots, x_n\}$$

Label set:

$$Y = \{0, 1\} \quad (0 = \text{normal}, 1 = \text{attack})$$

Define model hypothesis: $h\theta(X)$

Logistic regression baseline:

$$h\theta(X) = \frac{1}{(1 + e^{-\theta^T X})} \quad (8)$$

Loss function:

$$J(\theta) = -\left(\frac{1}{m}\right) \sum [y \log(h\theta(x)) + (1 - y) \log(1 - h\theta(x))] \quad (9)$$

Gradient descent update:

$$\theta := \theta - \alpha \nabla_{\theta} J(\theta)$$

Detection threshold:

$$\text{if } h\theta(X) \geq \delta, \text{ predict intrusion}$$

Anomaly score:

$$s(x) = \|X - \hat{X}\|^2 \text{ (autoencoder)} \quad (10)$$

Decision:

$$\text{if } s(x) > \tau, \text{ flag anomaly}$$

Precision:

$$P = \frac{TP}{(TP + FP)} \quad (11)$$

Recall:

$$R = \frac{TP}{(TP + FN)} \quad (12)$$

F1-score:

$$F1 = \frac{(2PR)}{(P + R)} \quad (13)$$

Final decision rule: Intrusion if $(h\theta(X) \geq \delta)OR (s(x) > \tau)$

III. Integration of Security Frameworks

A. Interoperability of blockchain, encryption, and AI systems

Blockchain, encryption, and AI can all work together through interoperability. This protects trust, privacy, and flexible intelligence in smart substations by allowing safe communication and defences that work together.

Theorem 1: *Let B represent blockchain-based integrity, E represent homomorphic encryption, and A represent AI-driven detection.*

Proof: Define blockchain integrity score:

$$IB = H(\Sigma tx)$$

where H = hash function, tx = transaction.

Define encryption security:

$$SE = P(m)$$

where P is probability that plaintext m remains confidential.

Define AI detection accuracy:

$$DA = \frac{TP}{(TP + FN)}. \quad (14)$$

System interoperability defined as:

$$S = f(IB, SE, DA). \quad (15)$$

Let combined resilience:

$$R = \alpha \cdot IB + \beta \cdot SE + \gamma \cdot DA, \text{ where } \alpha + \beta + \gamma = 1. \quad (16)$$

If $IB \geq \theta_1, SE \geq \theta_2, DA \geq \theta_3$, then $R \geq \min(\theta_1, \theta_2, \theta_3)$.

Blockchain ensures immutability:

$$IB = \log_2(|tx| + 1). \quad (17)$$

Encryption ensures confidentiality: $SE = 1 - Pe$, where Pe = probability of successful attack.

B. Real-time monitoring and adaptive response mechanisms

Real-time tracking makes it easier to know what's going on, and adaptable reaction mechanisms fight threats on the fly, keeping operations running smoothly and making sure the substation can handle new cyber risks.

Theorem 2: *Let $M(t)$ denote real-time monitoring effectiveness, and $A(t)$ denote adaptive response strength at time t .*

If $A(t)$ is a function of $M(t)$, then cyber risk probability decreases exponentially over time.

Proof: Define monitoring function:

$$M(t) = \sum f_i(t),$$

where f_i are detection features.

Detection probability:

$$Pd(t) = 1 - \exp(-\lambda M(t)). \quad (18)$$

Adaptive response defined as:

$$A(t) = \kappa Pd(t), \text{ where } \kappa > 0. \quad (19)$$

Define cyber risk probability:

$$Pr(t) = \exp(-\mu A(t)), \mu > 0. \quad (20)$$

Substitute $Pd(t)$:

$$Pr(t) = \exp(-\mu \kappa (1 - \exp(-\lambda M(t)))). \quad (21)$$

If $M(t)$ increases with time, $Pd(t)$ increases monotonically.

Since $A(t) \uparrow \Rightarrow Pr(t) \downarrow$, risk decreases exponentially.

Define resilience index:

$$R(t) = 1 - Pr(t). \quad (22)$$

$$\text{Then } R(t) = 1 - \exp(-\mu \kappa (1 - \exp(-\lambda M(t)))). \quad (23)$$

IV. Result and Analysis

The comparison results show that AI-driven breach detection works better than traditional methods, with the best detection accuracy (94.5%) and resistance index (89.2%), and only middling delay, performance comparison of security approaches shown in figure 2.




Figure 2
Performance Comparison of Security Approaches Across Key Metrics

Blockchain-based integrity provides high reliability (86.5%) and better accuracy, but it also causes more delay.




Figure 3
AI-driven Intrusion Detection: Contribution of Key Metrics

Homomorphic encryption gives us the most protection, but it also takes the most time (142 ms) and resources. Traditional routers are good at reducing delays, but they are not very good at accuracy or resilience (show in figure 3). The new methods that are combined make the substation setting safer and fairer.

V. Conclusion

Modern smart grids depend on intelligent network substations to keep them running smoothly. However, cyber threats are growing and could compromise data privacy, security, and availability. This research looked at problems with communication protocols, integrating the Internet of Things (IoT), and cloud-based systems. It also looked at more advanced security measures like blockchain, homomorphic encryption, AI-driven breach detection, and zero-trust designs. When these options are put together, they can make substations more resilient, reliable, and private.

References

- [1] I. Priyadarshini, R. Kumar, R. Sharma, P. K. Singh, and S. C. Satapathy, "Identifying cyber insecurities in trustworthy space and energy sector for smart grids," *Comput. Electr. Eng.*, vol. 93, pp. 107204 (2021).
- [2] P. Y. Kong, "A review of quantum key distribution protocols in the perspective of smart grid communication security," *IEEE Syst. J.*, vol. 16, pp. 41–54 (2020).
- [3] O. M. Butt, M. Zulqarnain, and T. M. Butt, "Recent advancement in smart grid technology: Future prospects in the electrical power network," *Ain Shams Eng. J.*, vol. 12, pp. 687–695 (2021).

- [4] D. Fan, Y. Ren, Q. Feng, Y. Liu, Z. Wang, and J. Lin, "Restoration of smart grids: Current status, challenges, and opportunities," *Renew. Sustain. Energy Rev.*, vol. 143, pp. 110909(2021).
- [5] K. Nisar, E. R. Jimson, M. Hijazi, and S. K. Memon, "A survey: Architecture, security threats and application of SDN," *J. Ind. Electron. Technol. Appl.*, vol. 2, pp. 64–69 (2019).
- [6] Y. Zhang and M. Chen, "Performance evaluation of Software-Defined Network (SDN) controllers using Dijkstra's algorithm," *Wirel. Netw.*, vol. 28, pp. 3787–3800 (2022).
- [7] M. M. Almazari, E. Taqieddin, A. S. Shatnawi, and Z. Al-Shara, "An evaluation of the RSA private keys and the presence of weak keys," *J. Discrete Math. Sci. Cryptogr.*, vol. 26, no. 8, pp. 2273–2284 (2023), doi: 10.47974/JDMSC-1670.
- [8] R. Santos, D. Souza, W. Santo, A. Ribeiro, and E. Moreno, "Machine learning algorithms to detect DDoS attacks in SDN," *Concurr. Comput. Pract. Exp.*, vol. 32, pp. e5402 (2020).
- [9] I. Mohan, M. Venkataraman, and K. Thilagavathi, "Investigating utilizations of harmonic univalent functions employing the Prabhakar fractional operator within specific categories," *J. Interdiscip. Math.*, vol. 27, no. 5, pp. 1099–1108 (2024).
- [10] C. D. Kokane, S. D. Babar, P. N. Mahalle, and S. P. Patil, "Word sense disambiguation: Mathematical modelling of adaptive word embedding technique for word vector," *J. Interdiscip. Math.*, vol. 26, no. 3, pp. 475–482 (2023).
- [11] H. Polat, M. Türkoğlu, O. Polat, and A. Şengür, "A novel approach for accurate detection of the DDoS attacks in SDN-based SCADA systems based on deep recurrent neural networks," *Expert Syst. Appl.*, vol. 197, pp. 116748 (2022).
- [12] A. Krishnan and E. Tanaka, "Exploring Quantum Computing Algorithms for Optimization Problems," *Int. J. Adv. Comput. Theory Eng.*, vol. 13, no. 1, pp. 7–11 (Apr. 2025).
- [13] H. Mahmood, D. Mahmood, Q. Shaheen, R. Akhtar, and W. Changda, "S-DPs: An SDN-based DDoS protection system for smart grids," *Secur. Commun. Netw.*, vol. 2021, pp. 1–19 (2021).

Received April, 2025