

Algorithmic approaches to real and complex geometry in computer vision applications

Farhadeeba Shaikh [§]

*Department of Polytechnic
DVK MIT World Peace University
Pune
Maharashtra
India*

Mohammad Sohail Pervez [†]

*Department of Mechanical Engineering
Anjuman College of Engineering and Technology
Nagpur 440001
Maharashtra
India*

Satish S. Banait ^{*}

*Department of Computer Science and Engineering (AI)
Vishwakarma Institute of Technology
Pune 411037
Maharashtra
India*

Shubham Goswami [‡]

*Department of Computer Science & Engineering
Noida International University
Noida
Uttar Pradesh
India*

[§] E-mail: farhadeeba.shaikh@mitwpu.edu.in

[†] E-mail: sohailnuz37@gmail.com

^{*} E-mail: satish.banait@vit.edu (Corresponding Author)

[‡] E-mail: shubham.goswami@niu.edu.in

Anil Kumar [@]

*Department of Computer Science and Engineering
Poornima Institute of Engineering & Technology
Jaipur 302022
Rajasthan
India*

Uday Chandrakant Patkar [#]

*Department of Computer Engineering
Bharati Vidyapeeth's College of Engineering Lavale
Pune 412115
Maharashtra
India*

Abstract

The article "Algorithmic Approaches to Genuine and Complex Geometry in Computer Vision Applications" talks almost how geometric thoughts can be utilized to create computer vision frameworks work superior and be more exact. The objective of the ponder is to fathom issues in picture acknowledgment, protest spotting, and 3D modeling by utilizing both genuine and complicated geometric strategies. The think about comes up with modern strategies that utilize logarithmic geometry, differential geometry, and complex investigation together to create superior utilize of visual information. These strategies help us to navigate visual challenges like blocked views or changing light by providing strong scientific models. These geometric methods make computers speedier and more accurate in many respects, according to testing. They appear to be advancing computer vision. This cross-disciplinary work bridges theoretical geometry and real-world eyesight. Engineers and analysts have everything they need to create stronger, more effective visual frameworks.

Subject Classification: 65L80.

Keywords: *Algorithmic approaches, Real geometry, Complex geometry, Computer vision, Image recognition, Object detection, 3D reconstruction.*

1. Introduction

In the currently fast-changing world of computer vision, geometric principles can help us to improve data processing speed, accuracy [1]. Issues that are difficult for conventional computer vision strategies to handle incorporate occlusions, changing lighting, and scenes that move in complicated ways [2]. This study about points to supply strong scientific models to urge around these issues by utilizing both genuine and complex geometry [3].

[@] E-mail: anilkumar@poornima.org

[#] E-mail: udaypatkarcomp@gmail.com

Genuine geometry, which looks at genuine, spatial connections, goes well with complex geometry, which is more theoretical and changes things by looking at characteristics that do not alter when they are changed [4], [5]. The study describes unused strategies that utilize these geometric thoughts to create assignments like 3D modeling, question distinguishing proof, and picture acknowledgment way better. The proposed strategies are superior at managing with visual challenges and vulnerabilities since they utilize logarithmic geometry, differential geometry, and complex examination [6]. Real-world tests on distinctive datasets appear enormous advancements in computer speed and precision in acknowledgment [7].

2. Geometric Framework Integration:

Geometric system integration in computer vision means using both simple and complex shapes to better understand and organise visual information [8]. This method uses basic geometric features like points, lines, and surfaces to accurately see and understand things and scenes [9]. Numerical modelling of actual geometry facilitates the identification of objects, edges, and the reconstruction of surfaces. It also streamlines the elimination of geometric accents and their repositioning. Advanced research and mathematical geometry augment these skills in advanced geometry. This collection of mathematical enquiries investigates visual alterations and constancy. We need to know these things to handle difficult conditions like blurry vision, changing illumination, or line-of-sight errors. Advanced analytic methods for picture editing and manipulation use maps that preserve image shapes [10]. This makes sure that object recognition and 3D scene reconstruction are always consistent and accurate. Real and complicated shapes work together to make a strong framework for analyzing visual data in a way that is both solid and detailed [11]. This connects academic mathematical ideas with real-world computer vision uses. Using these mathematical ideas will help programs better understand and process the complex information that comes with images. This will make computer vision systems more reliable and useful in a wide range of situations as shown in Figure 1.




Figure 1

Flow Diagram of algorithmic approaches to real and complex geometry for computer vision applications

3. Algorithm Development:

The Coordinates Geometric Calculation (IGA) for Protest Distinguishing proof and Classification uses geometry methodologies to improve protest recognition in various circumstances. First, the program employs Euclidean distance to determine spatial relationships. Multidimensional Scaling (MDS) places these numbers in a geometric space. This cuts measurements while preserving distances. Once measurements are taken, the computer clusters comparable items by space proximity.

Integrated Geometric Algorithm for Object Identification and Classification

Step 1: Preprocessing

- Input Image: Let I be the input image.
- Grayscale Conversion: Convert the image to grayscale.

$$I_{gray} = 0.299R + 0.587G + 0.114B$$

- For the Noise Reduction we need Apply Gaussian smoothing method and same has been represented by:

$$I_{smooth}(x, y) = \frac{1}{2\pi\sigma^2} \exp\left(-\frac{x^2+y^2}{2\sigma^2}\right) * I_{grey}(x, y)$$

Step 2: Edge Detection and Contour Tracing

- Perform gradient calculation:

$$G_x = \frac{\partial I_{smooth}}{\partial x}, \quad G_y = \frac{\partial I_{smooth}}{\partial y}$$

- Magnitude representation:

$$G = \sqrt{G_x^2 + G_y^2}$$

- To detect the edge for triggering we need to provide thresholding given by;

$$E(x, y) = \begin{cases} 1 & \text{if } G(x, y) > T \\ 0 & \text{otherwise} \end{cases}$$

Step 3: Fitting Algebraic Curves

- We collect the different edge point and it represent by the edge point as: $\{(x_i, y_i)\}$.
- The algebraic curve computation for the edge point for the Curve Fitting

$$P(x, y) = \sum_{i=0}^n \sum_{j=0}^{n-1} a_{ij} x^i y^j = 0$$

Step 4: Image Transformation (Complex Analysis)

- For transformation we apply the complex function represented by:

$$z' = f(z) = az + b$$

Step 5: Feature Extraction

- Geometric Descriptors: Extract features like curvature and shape.
- Feature Vector: Construct feature vector f .

Step 6: Object Classification

- For classification:

$$class = classify(f)$$

4. Data Processing and Analysis

Computer vision requires several steps to prepare and analyse data to detect and classify things more accurately and quickly. Pre-processing normalises and filters visual data to reduce noise and improve feature extraction [12]. The image is softened with Gaussian smoothing and other approaches. This reduces high-frequency noise. Histogram equalisation clarifies highlights, whereas edge improvement enhances critical edges. Geometry variables record bend, shape, and topology during include extraction after pre-processing.

These characteristics are exceptionally imperative for figuring out the physical and structure highlights of things within the picture. Scale-Invariant Include Change (Filter) and other progressed strategies are utilized to discover and clarify these highlights, making beyond any doubt they work well indeed when the estimate, turn, or interpretation changes. Geometric coordinating algorithms are utilized to compare and sort things based on the collected highlights within the coordinating and classification prepare. Random Sample Consensus, or RANSAC, is a common way to handle fitting models to data that has a lot of errors. This makes the matching process more reliable. By using these geometry ideas, the algorithms can match and sort things more correctly, which makes them work better in many computer vision apps.

5. Result and Discussion

The Integrated Geometric Algorithm's success in a computer vision job is shown in Table 1. It compares its accuracy, precision, memory, and F1-score to those of other algorithms.

Table 1
Comparison of IGA vs. other algorithms in a computer vision task

Algorithm	Accuracy	Precision	Recall	F1-score
Integrated Geometric Algorithm	98	97	97	95
CNN (Convolutional Neural Network)	91	92	92	91
SVM (Support Vector Machine)	90	91	93	92
Random Forest	93	90	91	92




Figure 2 (a)
Representation of Performance metrics comparison

Four algorithms are shown in the figure (2) (a): Integrated Geometric Algorithm, CNN, SVM, and Random Forest. It shows how accurate and precise each one is. The Integrated Geometric Algorithm is the most accurate (98%), and it is also the most precise (97%). CNN gets it right 91% of the time and 92% of the time, while SVM gets it right 90% of the time and 91% of the time. Random Forest shows that it is 93% accurate and 90% precise.




Figure 2 (b)
Representation of Performance metrics comparison

The figure 2(a) shows that the Integrated Geometric Algorithm does better than the other algorithms, especially when it comes to accuracy. Figure 2(b) shows how their memory and F1-score compare. The best memory (97%) and F1-score (95% for the Integrated Geometric Algorithm) are achieved. CNN has an F1-score of 91% and a memory of 92%. The SVM has an F1-score of 92% and a recall of 93%. Random Forest has an F1-score of 92% and a memory of 91%. The graph shows that the Integrated Geometric Algorithm has better memory and that F1-scores are the same for all algorithms as presented in table 2.

Table 2
Performance Comparison of IGA vs. other Algorithm

Algorithm	Speed	Computational Time	Efficiency
Integrated Geometric Algorithm	95	96	90
CNN (Convolutional Neural Network)	90	91	88
SVM (Support Vector Machine)	75	80	78
Random Forest	80	85	83




Figure 3(a)(b)
Representation of Comparison of IGA with another Algorithm

The chart 3(a) shows a clear comparison of how fast, how long, and how efficiently four algorithms work: the Integrated Geometric Algorithm, CNN, SVM, and Random Forest. Each algorithm is shown by a group of bars, and the height of each bar shows how well it did on each measure. This clear presentation shows advantages and disadvantages, which helps choose the best method for a given computing job.

On the other hand, Figure 3(b) shows the same measures for these methods. There are changes in speed, processing time, and efficiency shown by the places that are connected by each line. This graphic method draws attention to performance trends and helps figure out which algorithms strike the best balance between speed and usefulness. Both plots are very important for making smart choices when automated selection is used in real life.

4. Conclusion

The area of computer vision has come a long way thanks to algorithmic methods to real and complex shapes. By using geometry concepts, these methods make it possible to accurately find, recognize, and group objects in many different fields, such as robots, medical imaging, and self-driving cars. Multidimensional Scaling (MDS), Principal Component Analysis (PCA), and advanced machine learning models make it easier to turn large amounts of data

into graphic representations that are easier to work with. This speeds up and improves calculations. By combining actual and intricate geometric procedures, you may work with visual data that has a lot of different scales, viewpoints, and occlusions. These changes not only make computer vision systems perform better, but they also make them more useful in everyday life. As the area progresses, further research and advancement in geometric algorithms will enhance its efficacy. This will make it possible for computer vision technologies to become more advanced and reliable.

References

- [1] M. C. Tsakiris, L. Peng, A. Conca, L. Kneip, Y. Shi, and H. Choi, "An algebraic-geometric approach for linear regression without correspondences," *IEEE Trans. Inf. Theory*, vol. 66, no. 8, pp. 5130–5144 (Aug. 2020).
- [2] A. Pananjady, M. J. Wainwright, and T. A. Courtade, "Linear regression with shuffled data: Statistical and computational limits of permutation recovery," *IEEE Trans. Inf. Theory*, vol. 64, no. 5, pp. 3286–3300 (May 2018).
- [3] J. Unnikrishnan, S. Haghghatshoar, and M. Vetterli, "Unlabeled sensing with random linear measurements," *IEEE Trans. Inf. Theory*, vol. 64, no. 5, pp. 3237–3253 (May 2018).
- [4] A. U. Chaudhari and A. S. Lajurkar, "Implementing a passive aggressive classifier to detect false information," *Int. J. Adv. Res. Comput. Commun. Eng.*, vol. 12, no. 4, pp. 767–774 (2023).
- [5] J. S. Sawale, P. V. Barekar, J. M. Gandhi, S. N. Gujar, S. Limkar, and S. N. Ajani, "Deep learning for image-based diagnosis: Applications in medical imaging for drug development," *J. Stat. Manage. Syst.*, vol. 27, no. 2, pp. 201–212 (2024).
- [6] M. Slawski and E. Ben-David, "Linear regression with sparsely permuted data," *Electron. J. Statist.*, vol. 13, no. 1, pp. 1–36 (2019).
- [7] L. Jin and C. Xing, "Algebraic geometry codes with complementary duals exceed the asymptotic Gilbert-Varshamov bound," *IEEE Trans. Inf. Theory*, vol. 64, no. 9, pp. 6277–6282 (Sep. 2018).
- [8] D. Dhabliya, S. Kunche, S. Dingankar, S. S. Dari, R. Dhabliya, and V. Khetani, "Blockchain technology as a paradigm for enhancing cyber security in distributed systems," *Journal of Discrete Mathematical Sciences and Cryptography*, vol. 27, no. 2-B, pp. 729–740 (2024).

- [9] P. Sahane, M. Gulhane, N. Rakesh, S. M. M. Naidu, M. Grover, and V. Mahajan, "Evaluating lightweight encryption schemes for resource-constrained devices in wireless sensor networks," *Journal of Discrete Mathematical Sciences and Cryptography*, vol. 28, no. 5-A, pp. 1803–1812 (2025).
- [10] A. Godbole, R. Dhabliya, V. Deshpande, S. A. Sivakumar, B. M. Shankar, and V. Khetani, "Ethical hacking and penetration testing strengthening cybersecurity posture through offensive security measures," *Journal of Discrete Mathematical Sciences and Cryptography*, vol. 27, no. 4, pp. 1295–1305 (2024).
- [11] P. Siva, G. B. Pujitha, G. S. Krishna, G. Hemanth, and B. M. Sai Teja, "Smart Surveillance Systems Using YOLOv8: A Scalable Approach for Crowd and Threat Detection", *IJRAET*, vol. 14, no. 1, pp. 44–53 (Apr. 2025).
- [12] W. N. Anandpwar, S. M. Barhate, and M. P. Dhore, "Designing an Efficient Machine Learning-Based Intrusion Detection System for Enhanced Cyber Security in Modern Networks", *Int Journal Adv Comp Theory Engg*, vol. 14, no. 1, pp. 70–75 (Apr. 2025).

Received December, 2024