

Mathematical modeling and simulation of traffic flow dynamics using nonlinear differential equations

Supriya Kumbhar [‡]

*Department of Mechanical Engineering
Indira College of Engineering & Management
Pune 410506
Maharashtra
India*

Shriraghavan Madbushi [†]

*Department of Industrial Internet of Things
St. Vincent Pallotti College of Engineering & Technology
Nagpur 441108
Maharashtra
India*

Shraddha Gugulothu [§]

*Department of Electronics Engineering
Yeshwantrao Chavan College of Engineering (YCCE)
Nagpur 441110
Maharashtra
India*

B. Yamuna ^{*}

*Department of Mathematics
Dayananda Sagar College of Engineering
Bangalore 560111
Karnataka
India*

[‡] E-mail: supriyashirke679@gmail.com

[†] E-mail: m.shriraghavan@gmail.com

[§] E-mail: shraddha26sangewar@gmail.com

^{*} E-mail: yamunab-maths@dayanandasagar.edu (Corresponding Author)

Varsha Yadav [@]

*Department of Computer Science and Engineering
Rungta College of Engineering and Technology
Rungta International Skills University
Bhilai 490024
Chhattisgarh
India*

Jyotsna Suryavanshi [#]

*Department of Engineering Science and Humanities
Vishwakarma Institute of Technology
Pune 411037
Maharashtra
India*

M. Sreenivasa Reddy ^{\$}

*Department of Mechanical Engineering
Aditya University
Surampalem 533437
Andhra Pradesh
India*

Abstract

Interactions occur between vehicle density, velocity, traffic demand and roadway capacity, creating complex, nonlinear traffic flow dynamics. This research proposes a mathematical modelling and simulation approach to traffic flow analysis based on non-linear differential equations. Basic relations between traffic density, flow and velocity are derived together with the fundamental conservation law for traffic moving along road networks. Different initial and boundary conditions are used to simulate traffic states numerically, using solution techniques. The model goes on to study the propagation of a shock wave and stop and go traffic conditions resulting from obstruction and congestion and changes in traffic density. The simulation results presented are used to show the temporal and spatial changes of traffic characteristics, and to identify the change from free-flow to congested traffic. The framework proposed here is an effective mathematical basis for traffic prediction, traffic congestion analysis, and transportation management applications.

Subject Classification: 34G20.

Keywords: Traffic flow dynamics, Nonlinear differential equations, Traffic density, Numerical simulation, Shock-wave modeling, Traffic congestion.

[@] E-mail: varsha.yadav@rungta.org

[#] E-mail: jyotsna.suryavanshi@vit.edu

^{\$} E-mail: dypc@adityauniversity.in

I. Introduction

Modern transportation networks have become much busier, with traffic congestion being a pressing issue, due to rapid urbanization, population growth and increased vehicle use. Hence, the dynamic characteristics of the traffic flow is crucial for the design of efficient roadways, minimization of travel delays, reduction of accident risk and intelligent transportation management [1, 2]. Under different operating conditions, mathematical models can be used to systematically represent the interactions between traffic density, vehicle velocity, traffic flow, and road capacity. Nonlinear differential equations are especially appropriate for the study of traffic systems since traffic systems have nonlinear responses, congestion transitions, wave propagation, and complex interactions that occur amongst vehicles [3, 4, 5]. The fundamental variables are density, flow rate, and average velocity, which are the fundamental descriptors of traffic flow. They determine if a roadway is free flow, transition, or congested conditions. The laws of conservation that are formulated in the form of differential equations describe the evolution of the number of vehicles over space and time, but do not change the total number of vehicles in the transportation system [6, 7]. Moreover, nonlinear formulations can be used to represent more realistically disturbances that create shock waves and recurring stop-and-go patterns. The aim of this study is to establish a mathematical model for the traffic flow dynamics based on nonlinear differential equations [8, 9, 10]. Numerical methods are used to approximate the solutions of the model under different traffic conditions. The outcome of the simulations is a quantitative assessment of the traffic behavior, traffic congestion formation, and propagation of shock waves and temporal variations, which can be used for traffic prediction, development of roadways, traffic congestion mitigation, and intelligent transportation control [11, 12].

II. Numerical Solution of the Nonlinear Differential Equations

The nonlinear traffic equations are numerically solved by discretization methods, which can approximately solve the density and velocity changes of the traffic to the stability of the roadways under dynamically changing traffic conditions, and consider the overall traffic behavior, reflect the complex traffic behavior of the roadway [13, 14].

Nonlinear Traffic Flow Equation

$$\frac{\partial \rho}{\partial t} + \frac{\partial [\rho v(\rho)]}{\partial x} = 0 \quad (1)$$

The traffic flow equation (1) is nonlinear and describes the basic dynamics of the evolution of vehicle density as a function of space and time. It defines the conservation state of traffic movement.

Density-Dependent Velocity Model

$$v(\rho) = v_f \left(1 - \frac{\rho}{\rho_{max}} \right) \quad (2)$$

The density-dependent velocity model is defined by Equation (2), with the velocity of vehicles gradually decreasing as the traffic density increases to the maximum traffic density on the roadway.

Nonlinear Traffic Flux

$$q(\rho) = \rho v_f \left(1 - \frac{\rho}{\rho_{max}}\right) \quad (3)$$

Density and velocity are combined to create a nonlinear traffic flux in equation (3) and represents the number of vehicles that traverse a location of a roadway within a given time period.

Spatial Discretization

$$\frac{\partial q}{\partial x} \approx \frac{q_{i+1}^n - q_i^n}{\Delta x} \quad (4)$$

The spatial discretization is added to equations (4) to approximate the changes in traffic flow among adjacent road segments. This change allows for the computation of the continuous nonlinear model at discrete spatial points.

Temporal Discretization

$$\frac{\partial \rho}{\partial t} \approx \frac{\rho_i^{n+1} - \rho_i^n}{\Delta t} \quad (5)$$

Also, equation (5) is used to discretize the temporal domain to estimate the difference in traffic density between the next simulation time step. These discretization procedures combine to form a representation of the governing partial differential equation that is manageable for numerical calculations.


Numerical Density Update

$$\rho_i^{n+1} = \rho_i^n - \left(\frac{\Delta t}{\Delta x}\right)(q_{i+1}^n - q_i^n) \quad (6)$$

Lastly, the updating mechanism for the numerical density is given by equation (6). It is based on the differences of traffic flux between adjacent spatial locations and current traffic density and it's able to calculate traffic density in the future. For this reason, the equation can be used to simulate the evolution of traffic, congestion, density propagation and dynamic roadway conditions in an iterative manner over subsequent time steps.

III. Traffic Flow System and Mathematical Formulation

The traffic flow system is mathematically defined by combining the density and velocity of the vehicles, their flow rate, the capacity of the roadway, and the nonlinear interactions between vehicles to accurately model realistic spatiotemporal vehicle flow patterns [15]. The framework for modeling dynamic traffic behavior is a nonlinear system as shown in Figure 1.


Figure 1
Mathematical Framework for Nonlinear Traffic Flow Modeling and Simulation
A. Traffic Density, Flow, and Velocity Relationships

Traffic flow, density and velocity are connected basic variables of the roadway, in which traffic flow and velocity have a direct effect on the overall traffic movement and level of congestion.

$$q = \rho v \quad (7)$$

$$v(\rho) = v_f \left(1 - \frac{\rho}{\rho_{max}} \right) \quad (8)$$

From the above it is evident that traffic flow is directly proportional to the density and average velocity, as shown in Equation (7). The linear-speed/density relationship is expressed as Equation (8), where vehicle speed will decrease as the density increases towards the maximum vehicle rate that the roadway can accommodate [16].

Flow-Density Relationship

$$q(\rho) = \rho v_f \left(1 - \frac{\rho}{\rho_{max}} \right) \quad (9)$$

These relations are combined in equation (9) to obtain a non-linear flow-density relation, which shows the dependence of traffic flow on density initially as it grows, but with the onset of congestion it becomes a decreasing function.

Critical Traffic Density

$$\rho_c = \frac{\rho_{max}}{2} \quad (10)$$

The critical traffic density that indicates the threshold between efficient traffic flow and congestion is calculated from equation (10).

Maximum Traffic Flow

$$q_{max} = \frac{vf\rho_{max}}{4} \quad (11)$$

The model assumes that the traffic flow is related to speed and density in a specific way, and equation (11) is used to calculate the maximum traffic flow possible, which corresponds to the capacity of the roadway. These quantities are significant in determining transportation condition under which the transportation infrastructure is maximally utilized.

Average Traffic Velocity

$$\bar{v} = \left(\frac{1}{N}\right) \sum_{i=1}^N v_i \quad (12)$$

The average traffic velocity in equation (12) is calculated using the speeds of the individual vehicles in the traffic stream observed.

Average Traffic Density

$$\bar{\rho} = \left(\frac{1}{L}\right) \int \rho(x, t) dx \quad (13)$$

Spatial integration is used in equation (13) to calculate the average traffic density for a given length of the roadway. These equations give quantitative measures of traffic conditions, thresholds of traffic congestion, estimates of roadway capacity, and numerical simulation of the nonlinear traffic-flow dynamics for varying densities and velocities.

B. Conservation Law for Traffic Flow

The conservation law describes the continuity of the vehicles in the vehicle system; it is used to mathematically model the evolution in density and flow of the vehicles through space and time by balancing the traffic flow that enters the roadways with the traffic flow that leaves the roadways.

Traffic Conservation Equation

$$\frac{\partial \rho}{\partial t} + \frac{\partial q}{\partial x} = 0 \quad (14)$$

The fundamental continuity condition is presented in equation (14) which states that the changes in traffic density is equal to the spatial changes in the traffic flow.

Conservation Equation with Flow Relationship

$$\frac{\partial \rho}{\partial t} + \frac{\partial(\rho v)}{\partial x} = 0 \quad (15)$$

The relationship between density and velocity is included in Equation (15) which relates the vehicle conservation directly to traffic motion.

Conservation Equation with Source Term

$$\frac{\partial \rho}{\partial t} + \frac{\partial q}{\partial x} = S(x, t) \quad (16)$$

The formulation is expanded by the addition of a source term to represent external effects like vehicles entering or leaving the network by ramps, intersections or access points as shown in Equation (16).

Integral Conservation Law

$$\frac{d}{dt} \int (x_1 \text{ to } x_2) \rho(x, t) dx = q(x_1, t) - q(x_2, t) \quad (17)$$

The integral form of the conservation law for the roadway section is given by equation (17). It has declared that the change in the number of total vehicles relies on the distinction between inflow and outflow vehicles at a specific time.

Vehicle Accumulation

$$\frac{dN}{dt} = q_{in} - q_{out} \quad (18)$$

Equation (18) also applies to vehicle accumulation, and is a simplified version of the vehicle storage model in a roadway section, with inflow and outflow rates.

Discrete Conservation Equation

$$\rho_i^{n+1} = \rho_i^n - \left(\frac{\Delta t}{\Delta x} \right) (q_{i+1}^n - q_i^n) \quad (19)$$

The continuous conservation equation is transformed into a discrete numerical version that can be simulated numerically using (19).

Conservation with Entry and Exit Rates

$$\frac{dN}{dt} = q_{in} - q_{out} + r_{in} - r_{out} \quad (20)$$

Last but not least, equation (20) explicitly includes more entry and exit rates. These equations, taken together, allow to model realistically traffic accumulation, vehicle conservation, boundary flows, roadway interactions and density evolution on dynamic transportation networks.

IV. Shock-Wave and Stop-and-Go Traffic Modeling

The traffic transitions associated with sudden changes in traffic flow from light to heavy conditions or the opposite are represented by shock-wave modeling, whereas the repeated acceleration and deceleration due to congestion, disturbances, density changes, driver behavior and roadway constraints are described by stop-and-go modeling.

$$w = \frac{q_2 - q_1}{\rho_2 - \rho_1} \quad (21)$$

$$x_{s(t)} = x_{s(0)} + wt \quad (22)$$

The speed of the shock-wave is determined by equation (21) which represents the difference between the traffic flow and density of two traffic states. By using the propagation speed of the shock wave, it is estimated that the spatial position of the shock wave can be obtained from equation (22) over time.

Nonlinear Velocity Dynamics

$$\frac{dv}{dt} = \alpha[V(\rho) - v] \quad (23)$$

In Equation (23) the actual vehicle speed is represented as a function of the desired speed with dynamics that are nonlinear, depending on the density conditions.

Optimal Velocity Function

$$V(\rho) = v_f \left(1 - \frac{\rho}{\rho_{max}} \right) \quad (24)$$

The optimal velocity function given by equation (24) shows that speed that can be achieved will decrease with traffic density.

Stop-and-Go Velocity Oscillation

$$v(t) = v_0 + A \sin(\omega t + \varphi) \quad (25)$$

The time velocity fluctuations described by equation (25) are periodic oscillations about an equilibrium velocity.

Density Oscillation

$$\rho(t) = \rho_0 + B \sin(\omega t + \theta) \quad (26)$$

The same applies to equation (26) which models density oscillations around the corresponding equilibrium traffic density. Their amplitude and frequency represent the strength and frequency of the congestion disturbances.

Traffic Flow During Oscillation

$$q(t) = \rho(t)v(t) \quad (27)$$

Lastly, equation (27) computes instantaneous traffic flow by multiplying oscillating density and velocity. These equations as a whole constitute a mathematical model for simulating congestion waves, roadway speed variations, density perturbations, traffic instability and stop-and-go phenomena under nonlinear roadway conditions.

V. Result and Discussion

The results of simulations show the dependence on density, velocity and flow and have been found to show congestion formation, propagation of shock-waves and stop and go behavior of the traffic, thus establishing the effectiveness of the model for comprehensive traffic analysis.

Table 1
Traffic Flow Characteristics under Different Density Conditions

Scenario	Traffic Density (veh/km)	Average Velocity (km/h)	Traffic Flow (veh/h)	Congestion Index	Travel Time (min)
S1	15	82.4	1236	0.18	12.6
S2	25	71.8	1795	0.31	14.4
S3	35	59.6	2086	0.46	17.3
S4	45	46.2	2079	0.61	22.1
S5	55	32.8	1804	0.76	31.2
S6	65	21.5	1398	0.89	47.6

As the traffic density increases, velocity, traffic flow, congestion and travel time all change, as shown in Table 1. The higher the density (from 15 to 65 veh/km), the lower the average velocity (from 82.4 to 21.5 km/h), which shows progressive congestion. The changes in density and velocity under traffic situations are shown in Figure 2.




Figure 2
Comparative Analysis of Traffic Density and Average Velocity under Different Traffic Flow Scenarios

Flow rates start to rise and peak at 2086 veh/h at S3, and then are reduced at higher densities. In the meanwhile, the congestion index jumps from 0.18 to 0.89, and the travel time gets significantly higher, making the transitions from free-flow to severely congested traffic conditions nonlinear.

VI. Conclusion

In this study, a mathematical modeling and simulation method for analyzing the traffic flow dynamics using nonlinear differential equations were introduced. The developed formulation included basic relationships between traffic density, flow, velocity, and vehicle conservation to model changing roadway conditions. The numerical solution methods allowed to make the nonlinear traffic behavior effectively approximated under the various operating conditions. The study of the propagation of shock waves showed that the transient changes in density and velocity play a role in the development of congestion and traffic disturbances. The stop-and-go modelling also showed the periodic fluctuations which are often seen under conditions of congestion. The simulation framework gives valuable insights in transitions between free-flow and congested states of traffic. In

summary, the proposed mathematical approach is useful to perform systematic traffic analysis and prediction. Real-time traffic data, heterogeneous vehicles, intelligent control strategies and complex road networks can be integrated in future research for increased applicability.

References

- [1] K. Aldwoah, F. A. Alqarni, O. Osman, L. M. Abdalgadir, A. Touati, and W. Adel, "Mathematical modeling and dynamical analysis of a nonlinear coupled stress-mitigation system with signed threshold-relative policy feedback and physics-informed neural network simulation," *Mathematics*, vol. 14, no. 12, Art. no. 2231 (2026), doi: 10.3390/math14122231.
- [2] A. Paliathanasis, "Symmetry analysis for the 2D Aw-Rascle traffic-flow model of multi-lane motorways in the Euler and Lagrange variables," *Symmetry*, vol. 15, no. 8, Art. no. 1525 (2023), doi: 10.3390/sym15081525.
- [3] R. M. Soliby and S. S. Jamaian, "Non-linearity flux of fractional transport density equation in traffic flow with solutions," *Smart Cities*, vol. 5, no. 4, pp. 1655–1669 (2022), doi: 10.3390/smartcities5040084.
- [4] S. V. Sadavarte, S. B. Sarwe, and R. V. Saraykar, "A special class of solutions for three dimensional steady state magnetohydrodynamics equations with nonzero boundary velocity," *Journal of Dynamical Systems and Geometric Theories*, vol. 22, nos. 1–2, pp. 87–98 (2025), doi: 10.47974/JDSGT-2024-010.
- [5] A. Kantaros, T. Ganetsos, E. Pallis, and M. Papoutsidakis, "From mathematical modeling and simulation to digital twins: Bridging theory and digital realities in industry and emerging technologies," *Applied Sciences*, vol. 15, no. 16, Art. no. 9213 (2025), doi: 10.3390/app15169213.
- [6] G. Nastasi, "Mathematical models and simulations," *Axioms*, vol. 13, no. 3, Art. no. 149 (2024), doi: 10.3390/axioms13030149.
- [7] T. Alghamdi, S. Mostafi, G. Abdelkader, and K. Elgazzar, "A comparative study on traffic modeling techniques for predicting and simulating traffic behavior," *Future Internet*, vol. 14, no. 10, Art. no. 294 (2022), doi: 10.3390/fi14100294.
- [8] M. L. Scutaru and C.-I. Pruncu, "Mathematical modeling and simulation in mechanics and dynamic systems, 2nd edition," *Mathematics*, vol. 12, no. 2, Art. no. 341 (2024), doi: 10.3390/math12020341.

- [9] L. Hong and L. Zhang, "Nonlinear dynamical model and analysis of emotional propagation based on Caputo derivative," *Mathematics*, vol. 13, no. 13, Art. no. 2044 (2025), doi: 10.3390/math13132044.
- [10] S. Y. Barykin, I. V. Kapustina, S. M. Sergeev, and V. K. Yadykin, "Algorithmic foundations of economic and mathematical modeling of network logistics processes," *Journal of Open Innovation: Technology, Market, and Complexity*, vol. 6, no. 4, Art. no. 189 (2020), doi: 10.3390/joit-mc6040189.
- [11] M. Khachumov and V. Khachumov, "Modeling the solution of the pursuit–evasion problem based on the intelligent–geometric control theory," *Mathematics*, vol. 11, no. 23, Art. no. 4869 (2023), doi: 10.3390/math11234869.
- [12] E. Sebastian and R. C. Poonia, "Entropy diagnostics for cryptographic key material from random circuit sampling," *Journal of Discrete Mathematical Sciences and Cryptography*, vol. 29, no. 2-B, pp. 1023–1032 (2026), doi: 10.47974/JDMSC-2641.
- [13] S. Cheon and J. Lee, "An enhanced hybrid-level interface-reduction method combined with an interface discrimination algorithm," *Mathematics*, vol. 11, no. 23, Art. no. 4867 (2023), doi: 10.3390/math11234867.
- [14] I. Fernández-Irisarri and M. Mañas, "Laguerre–Freud equations for the Gauss hypergeometric discrete orthogonal polynomials," *Mathematics*, vol. 11, no. 23, Art. no. 4866 (2023), doi: 10.3390/math11234866.
- [15] V. Tsybulin and P. Zelenchuk, "Predator–prey dynamics and ideal free distribution in a heterogeneous environment," *Mathematics*, vol. 12, no. 2, Art. no. 275 (2024), doi: 10.3390/math12020275.
- [16] C.-L. Chiu, P. Huang, M.-Y. Day, Y. Ni, and Y. Chen, "Mastery of 'monthly effects': Big data insights into contrarian strategies for DJI 30 and NDX 100 stocks over a two-decade period," *Mathematics*, vol. 12, no. 2, Art. no. 356 (2024), doi: 10.3390/math12020356.

Received April, 2026