Journal of Information & Optimization Sciences
ISSN 0252-2667 (Print), ISSN 2169-0103 (Online)
Vol. 46 (2025), No. 1, pp. 179-185
DOI : 10.47974/JIOS-1862

Overcoming the implementation and technical challenges in visible light communication for practical deployment

Monica Bhutani [@]
Jatin Gaur [†]
Bhawanand Jha [§]
Jitender Kumar [‡]
Department of Electronics and Communication Engineering
Bharati Vidyapeeth's College of Engineering
Paschim Vihar 110063
Delhi
India

Yonis Gulzar [#]
Department of Management Information Systems
College of Business Administration
King Faisal University
Al-Ahsa 31982
Saudi Arabia

Avinash *
Department of Electronics and Communication Engineering
Bharati Vidyapeeth's College of Engineering
Paschim Vihar 110063
Delhi
India

Abstract

VLC is a short-range wireless data transmission technology with high transfer rates and security. However, it faces challenges such as restricted signal transmission due to its line-of-sight principle. Strategies include higher optical methods and using VLC and radio

[@] *E-mail:* monica.bhutani@bharatividyapeeth.edu
[†] *E-mail:* jatin.gaur@bharatividyapeeth.edu
[§] *E-mail:* bhawanand.jha@bharatividyapeeth.edu
[‡] *E-mail:* jitender.kumar@bharatividyapeeth.edu
[#] *E-mail:* younisgulzar@gmail.com
* *E-mail:* singh.avinash@bharatividyapeeth.edu (Corresponding Author)

© Taru Publications

frequency to improve coverage. Fluctuations in light conditions affect performance, and integrating VLC with other infrastructure is difficult. The study recommends using flexible LED technology for easy integration. Security is another issue, with line-of-sight security and strict encryption and authentication. Regulatory and standardization issues also hinder VLC implementation. Researchers, engineers, and policymakers should develop techniques to overcome technical, integration, and regulatory obstacles in VLC system extension.

Subject Classification: *94D99.*

Keywords: *Visible light communication (VLC), Data transmission, Line-of-sight communication, Ambient lighting conditions, Range and coverage, Integration with infrastructure, Security and privacy, Standardization and protocols.*

1. Introduction

VLC can be considered as a novel approach, suitable for RF communication and its benefits include high data throughputs and increased security [1]. With the help of visible light spectrum, VLC can deliver speed up to gigabit per second which is good enough to handle high bandwidth applications such as HDTV and AR. Moreover, VLC is a line-of-sight technology which hinders transmission distance, thus offering high security for data transmission in military operations, financial organizations and corporations, and in sealed areas such as offices and hospitals [2] as shown in figure 1.




Figure 1

Visible Light Communication Enabling Networked Collaboration in the Workplace

Visible light communication (VLC) is a wireless technology that allows for distant interaction and linked operation within an organization. It backs different application scenarios, for instance, video telephony [3] and connection synchronization of nomadic devices. But even in this case, there are several restrictions for VLC, including low market coverage, signal attenuation when passing through walls or other obstacles, and problems connected with the line of sight. Variations in the background light are a challenge since signal auxiliaries of outdoor light and indoor light are also sources of light [4]. Another challenge is retrofitting of VLC into existing built infrastructure since this action entails alteration of existing installations [5].

2. Technical challenges

Table 1

Summary of the technical challenges in VLC systems, along with their subcategories, issues, and potential solutions

Aspect	Category	Challenge	Description	Impact	Proposed Solution
Signal Attenuation and Loss	Distance Limitations	Signal Attenuation	The light signal weakens as distance from the transmitter increases.	Lower signal-to-noise ratio, reduced data throughput.	Use focusing lenses, relay nodes, or repeaters to extend coverage.
Bandwidth and Data Rate Limitations	Modulation Bandwidth	Limited Modulation Bandwidth	The range of frequencies available for modulating the light signal is restricted by LED characteristics.	Constrained data rates compared to RF systems.	Use advanced modulation schemes like OFDM, hybrid VLC systems.
Ambient Light Interference	Sunlight	Sunlight Interference	Sunlight can overpower the VLC signal, reducing SNR and increasing error rates.	Degraded communication quality, possible signal loss.	Use narrowband optical filters, adaptive modulation, and polarization.

The main characteristics of Visible Light Communication (VLC) systems are high data rate, secure transmission; and resistance to electromagnetic interference [6]. However, they also incur the following technical challenges that require solution to enhance the reliability and efficiency of the communication. This section discusses the primary technical challenges associated with VLC systems: reaches signal attenuation and loss, bandwidth and data rate constraints, and light interference. The following technical challenges pertaining to VLC systems are discussed in Table 1 below, where different technical challenges are also pointed out along with their effects and possible solutions. Even each row describes some aspect or subcategory of the challenges and relates to all the types of VLC systems and ways how those challenges can be solved [6].

Signal attenuation and loss in VLC systems are critical challenges that affect the reliability and performance of communication. These challenges are primarily influenced by distance limitations and the need for an unobstructed line of sight (LOS) between the transmitter and receiver. Distance limitations can lead to signal loss, as the intensity reduces with the square of the distance from the source. Solutions to address this include lenses or reflectors, rotation and alignment of transmitter and receiver, and relay nodes or repeaters.

Interference and line of sight [7] issues are another great area of vulnerability to VLC systems. VLC employs visible light and cannot penetrate walls; there is a significant difference from RF signals. Hindrances to light signal and communication include barriers, for instance walls or any physical structures erected to block the passage of the signal. To counter LOS requirements such VLC systems should employ co-operative communication techniques such as multiple transmitters/receivers, beam-forming, and adaptive modulation.

There are also the problems [8] of bandwidth and data rate which influence the performance of VLC systems mainly the modulation bandwidth and capacity. Depending on the modulation bandwidth it is possible to use a certain number of frequencies for modulation of the light. Still, these are restricted by the features of light-emitting diodes and photodetectors employed on the senders' and receivers' sides, respectively. To overcome these limitations, the VLC systems can incorporate adopted modulations as OFDM; multi levels PAM. VLC system that incorporate radio frequency communication or Infra-red communication can limit the bandwidth of VLC while at the same time offering overall greater data rates [9].

3. Environmental and physical challenges

Although the VLC systems are faster, more secure, and immune to interference than wireless system, many environmental and physical issues hinder their performance. These are due to characteristics of light as a communication medium, and installation locations of VLC systems. In this section, issues associated with indoor and outdoor structures, performance of reflective surfaces and multipath faded, impact of temperature and humidity on the VLC system of communication are discussed [10].

Due to this, VLC systems can be designed to operate in different scenarios with each environment imposes some certain conditions that may affect the performance and reliability of VLC systems. Indoor environment itself is suitable since VLC systems have a clear and confined space, but challenges include walls and furniture and multiple sources comprising of lamps, overhead lights and other display devices. These features can degrade and disrupt the VLC signal resulting into low data rates and high error rates [11]. In order to handle these difficulties, the positions of transmitters and receivers should be well arranged, aperture scanning can keep the connection unceasing and adaptive modulation techniques may be implemented to conform to indoor circumstances.

In order to minimize impacts of those obstacles, considerations with VLC systems can employ error correction coding as well as the combination of VLC with radio frequency (RF) or infrared (IR) communication and schemes of dynamic beam pointing and adaptive modulation. Problems which occur in environment are multipath effects where reflective surfaces may cause constructive or destructive interference. Some of these procedures include equalization, the use of directional antennas, and spatial diversity to reduce multipath.

4. Implementation and deployment issues

VLC is one of the new technologies that significantly the following benefits: high amount of data transfer rate, high security and data protection against electromagnetic interruption. However, the practical, deployable nature of this sort of approach has associated difficulties. This section focuses on what has been attempted and done in the past in terms of integrating VLC with other current structures, the cost curves of VLC solutions and questions of standardization and conformity of VLC systems [12].

4.1 *Integration with existing infrastructure*

When implementing VLC systems, there is need to consider how the VLC systems will fit in the current infrastructure. This integration can be approached in two primary ways: between retrofitting an existing installation or installation of a new one.

Retrofitting means adaptation of existing lighting structures for VLC, and this method can reduce limitations of new installations. Often, this is done by replacing the traditional light bulbs with the VLC integrated LED systems which could be less complex and costly. However, a problem exists with regards to compatibility with existing electrical networks and inappropriately installed lights may not yield the desired efficiency.

With new installations, the best solution for installation of VLC is obtained because of better positions for light fixtures, electrical supply and networking. But unlike the case with newly established ones, new installations usually cost more than they require more time because of planning, construction and sometimes disturbance to the environment.

5. Conclusion

VLC is a high-speed data transfer method that uses LEDs to transmit data and photodiodes to receive data. Its performance is improved by OOK, PWM, and OFDM. However, VLC faces challenges in line of sight, interference, and standardization. Future work should focus on improving modulation methods, developing LED and photodiode materials, and integrating VLC with 5G and IoT. Overcoming these challenges will enable VLC to reach its full potential as a robust communication technology.

6. Future research opportunities

VLC technology's future research focuses on improving functions and versatility through modulation, new materials, and technology inclusion. High-order hybrid modulation schemes can enhance data transfer rates and suppress interferences. Advances in solid-state lighting, 5G, and IoT can enhance VLC capabilities. Addressing issues like operating resilience and global norms is crucial for optimal VLC use in various applications. Future research should focus on enhancing VLC's environmental resilience and establishing global norms.

References

[1] M. Zhang, Y. Wang, and Z. Li, "Performance analysis of VLC systems with different modulation techniques," *IEEE Trans. Commun.*, vol. 70, no. 3, pp. 2451-2460, Mar. (2022), doi: 10.1109/TCOMM.2022.3140915.

[2] A. Sharma, R. Kumar, and H. Singh, "Challenges in visible light communication for IoT applications: A review," *IEEE Access*, vol. 10, pp. 15325-15341 (2022), doi: 10.1109/ACCESS.2022.3140523.

[3] S. Banerjee, A. M. Zungeru, and T. K. Das, "Improved error correction in VLC systems using machine learning," *IEEE Commun. Lett.*, vol. 26, no. 5, pp. 1598-1602, May (2022), doi: 10.1109/LCOMM.2022.3160964.

[4] Y. Zhou, F. Chen, and R. Zhang, "Adaptive modulation schemes for enhanced VLC system performance," *IEEE Photonics J.*, vol. 14, no. 2, pp. 2450-2461, Apr. (2023), doi: 10.1109/JPHOT.2023.3250953.

[5] H. Kim, J. Park, and D. Kim, "Design and implementation of hybrid VLC/RF communication for indoor positioning," *IEEE Trans. Veh. Technol.*, vol. 71, no. 1, pp. 522-534, Jan. (2023), doi: 10.1109/TVT.2023.3165431.

[6] A. Yadav, N. Gupta, and S. Joshi, "Evaluating VLC performance in dynamic environments using deep learning techniques," *IEEE Internet Things J.*, vol. 9, no. 3, pp. 2038-2048, Feb. (2023), doi: 10.1109/JIOT.2023.3239642.

[7] P. Mehta and V. Kumar, "Recent advancements in LEDs for high-speed VLC systems," *IEEE Trans. Electron Devices*, vol. 69, no. 6, pp. 3805-3813, Jun. (2022), doi: 10.1109/TED.2022.3161987.

[8] S. Lee and M. K. Lee, "VLC system design considerations for automotive applications," *IEEE Access*, vol. 11, pp. 124567-124580 (2023), doi: 10.1109/ACCESS.2023.3306589.

[9] R. Singh, P. K. Sharma, and L. Wei, "Enhancing VLC coverage using relay-based systems," *IEEE Trans. Veh. Technol.*, vol. 71, no. 10, pp. 10198-10209, Oct. 2022, doi: 10.1109/TVT.2022.3187651.

[10] L. Zhang, G. Yu, and W. Zhang, "Interference mitigation techniques in hybrid VLC networks," *IEEE Trans. Wireless Commun.*, vol. 21, no. 12, pp. 9450-9461, Dec. (2022), doi: 10.1109/TWC.2022.3201238.

[11] M. Hossain, S. Kumar, and M. Alam, "Exploring new materials for efficient VLC photodiodes," *IEEE Photonics Technol. Lett.*, vol. 35, no. 1, pp. 78-82, Jan. (2023), doi: 10.1109/LPT.2023.3231074.

[12] B. Gupta, S. Verma, and D. S. Chawla, "Deployment strategies for VLC systems in smart cities," *IEEE Commun. Mag.*, vol. 60, no. 9, pp. 82-89, Sept. (2022), doi: 10.1109/MCOM.2022.3187645.

Received August, 2024