Journal of Information & Optimization Sciences
ISSN 0252-2667 (Print), ISSN 2169-0103 (Online)
Vol. 47 (2026), No. 5-A, pp. 1851–1860
DOI : 10.47974/JIOS-2277

Implementing fuzzy control systems in automotive engineering for optimization

Manish K. Assudani [†]
Department of Computer Science & Engineering
Anjuman College of Engineering & Technology
Nagpur 440001
Maharashtra
India

Kumari Shipra *
School of Engineering & Technology
Noida International University
Greater Noida 203201
Uttar Pradesh
India

Archana Haribhau Bhapkar [§]
Department of Engineering Science and Humanities
Vishwakarma Institute of Technology
Pune 411037
Maharashtra
India

R. Arivukkodi [‡]
Department of Computer Science
Meenakshi College of Arts and Science
Meenakshi Academy of Higher Education and Research
Chennai 600078
Tamil Nadu
India

[†] *E-mail:* **mkasudani@gmail.com**
* *E-mail:* **kumari.shipra@niu.edu.in (Corresponding Author)**
[§] *E-mail:* **archana.bhapkar@vit.edu**
[‡] *E-mail:* **rarivukkodi@gmail.com**

© Taru Publications

Jambi Ratna Raja Kumar [@]
Department of Computer Engineering
Genba Sopanrao Moze College of Engineering
Balewadi
Pune 411045
Maharashtra
India

Abstract

This paper represent the fuzzy control systems can be used in automobile engineering to improve important parts of a car like the engine's performance, gas mileage, and stability control. In this study, a fuzzy control system for automobile uses is created by using fuzzy logic's built-in ability to deal with uncertainty and nonlinearities. Using advanced optimization methods like genetic algorithms and particle swarm optimization together improves the accuracy of control and the flexibility of the system even more. The approach shows big changes in how well controls work in different kinds of situations. To make car systems more reliable and efficient, the results show that fuzzy control systems mixed with optimization methods work well.

Subject Classification: *03B52.*

Keywords: *Fuzzy control, Automotive optimization, Genetic algorithms, Particle swarm optimization, System stability.*

I. Introduction

Automotive tech has changed quickly as people want safer, more fuel-efficient, and better performing cars. The intrinsic errors and complex dynamics in car systems make it hard for traditional control systems, which are often built on accurate mathematical models, to deal with them [1]. Changes in the surroundings, wear on the parts, and driver behaviour make these problems more complicated, which makes normal control methods less useful. Fuzzy control systems are a hopeful option because they work like humans do when they think and make decisions, so they can handle vague and unclear data well [2]. Fuzzy logic controls describe complicated systems without needing accurate mathematical representations. They do this by using language factors and rule-based reasoning. Because it is so flexible, fuzzy control is great for use in cars for things like managing the engine, controlling how much gas the car uses, and keeping the car stable [3]. But making a fuzzy control system that works well involves carefully setting membership functions and rule sets, which can take a lot of time and lead to performance that isn't as good as it could be. Adding optimization methods like genetic algorithms and particle swarm optimization to fuzzy control has become popular as a way to deal with these problems [4], [5].

[@] *E-mail:* `ratnaraj.jambi@gmail.com`

These metaheuristic methods help simplify the setting process, which makes the controller more accurate and the system more stable [6], [7].

II. Fuzzy Control System Fundamentals

Fuzzy control systems use language factors and membership functions along with fuzzy logic to deal with doubt and imperfect thinking. Figure 1 shows multicolor diagram illustrating key components of fuzzy control system [8], [9].




Figure 1
Overview of Fuzzy Control System Components

They use a set of if-then rules to connect inputs and outputs, which lets we handle complicated, nonlinear systems without having to use exact mathematical models. Because they are so flexible, they are perfect for use in automobile settings that are always changing and unsure [10], [11].

Fuzzification of Input Variables

$$\mu_{A(x)}: X \rightarrow [0,1] \quad (1)$$

Membership function μ_A(x) maps a crisp input x to a fuzzy degree of belonging between 0 and 1.

Equation 2: Fuzzy Set Definition

$$A = \{(x, \mu_A(x)) \mid x \in X\} \quad (2)$$

Fuzzy set A is defined by all elements x with their membership degrees μ_A(x) in the universe X.

Equation 3: Fuzzy Rule Base (If-Then Rules)

$$R_i: If\ x_1 is\ A_1^i and\ \ldots\ then\ y\ is\ B^i$$

Each fuzzy rule relates fuzzy input conditions A_1^i, ... to a fuzzy output set B^i.

Equation 4: Rule Activation (Firing Strength)

$$w_i = \min\left(\mu_{\{A_1^i\}(x_1)}, \mu_{\{A_2^i\}(x_2)}, \ldots \right) \tag{3}$$

The firing strength w_i is the minimum membership degree of all input conditions for rule i.

Equation 5: Aggregation of Rule Outputs

$$\mu_{B(y)} = \max_i \left(w_i \wedge \mu_{\{B^i\}(y)} \right) \tag{4}$$

Aggregate output membership μ_B(y) is the maximum of all rule consequents clipped by their firing strengths.

Equation 6: Defuzzification (Centroid Method)

$$y* = \frac{\left(\int y \, \mu_{B(y)dy} \right)}{\left(\int \mu_{B(y)dy} \right)} \tag{5}$$

Defuzzified output y* is the centroid of the aggregated output fuzzy set, converting fuzzy output to a crisp value.

Equation 7: Fuzzy Inference Function

$$f: (x_1, x_2, \ldots) \rightarrow y*$$

The fuzzy inference maps input variables x_1, x_2, ... to a crisp output y* through fuzzy reasoning.

Membership Function Example (Gaussian)

$$\mu_{A(x)} = \exp\left(-\frac{(x-c)^2}{(2\sigma^2)} \right) \tag{6}$$

Gaussian membership functions model smooth fuzzy sets using center c and width σ parameters.

Rule Base Output Combination

$$y = \frac{\Sigma_{\{i=1\}}^{N} (w_i y_i)}{\Sigma_{\{i=1\}}^{N} w_i} \tag{7}$$

Weighted average output uses firing strengths w_i and rule outputs y_i for defuzzification in Takagi-Sugeno systems.

Equation 10: Error Signal for Controller Tuning

$$e(t) = r(t) - y(t) \tag{8}$$

Error e(t) is the difference between desired reference r(t) and system output y(t), used for optimization.

III. Methodology

A. *Selection of automotive control problem(s) for optimization*

Engine performance, fuel economy, and stability control are some of the most important vehicle control problems that are being looked at [12], [13]. These places have a big effect on the safety, pollution, and costs of running a car. By choosing these problems, focused optimisation with fuzzy control can be used to deal with nonlinear dynamics and errors [14].

Define Input Variables

$$X = \{x_1, x_2, \dots, x_m\}$$

Input vector X represents sensor or system measurements such as speed, temperature, and throttle position for automotive control.

Equation 12: Define Output Variables

$$Y = \{y_1, y_2, \dots, y_n\}$$

Output vector Y contains control signals like fuel injection rate, ignition timing, or braking force for optimization.

Define Membership Functions for Inputs

$$\mu_{\{A_j\}(x_i)}: X_i \rightarrow [0,1] \tag{9}$$

Each input x_i maps to fuzzy sets A_j through membership functions quantifying the degree of belonging.

Define Membership Functions for Outputs

$$\mu_{\{B_k\}(y_l)}: Y_l \rightarrow [0,1] \tag{10}$$

Output variables are fuzzified similarly using membership functions defining control levels (e.g., low, medium, high).

Construct Fuzzy Rule Base

$$R_r: If\ x_1 is\ A_1^r and\ \dots\ then\ y_l is\ B_l^r$$

Rules link fuzzy input conditions to fuzzy output conclusions, representing expert knowledge for system control.

Compute Rule Firing Strength

$$w_r = \min_i \mu_{\{A_i^r\}(x_i)} \tag{11}$$

Rule activation w_r is the minimum membership among all inputs in the antecedent part of rule r.

Evaluate Rule Output

$$\mu'_{\{B_l^r\}}(y_l) = w_r \wedge \mu_{\{B_l^r\}(y_l)}$$

Output membership function clipped by firing strength gives fuzzy control output from each rule.

Aggregate Outputs

$$\mu_{\{B_l\}(y_l)} = \max_r \mu'_{\{B_l^r\}}(y_l) \quad (12)$$

Aggregate all rule outputs per output variable by taking the maximum membership across rules.

Defuzzification (Centroid Method)

$$y_l^* = \frac{\left(\int y_l \mu_{\{B_l\}}(y_l) dy_l\right)}{\left(\int \mu_{\{B_l\}}(y_l) dy_l\right)}$$

Convert fuzzy outputs to crisp values by calculating centroid of aggregated membership functions.

Formulate Objective Function for Optimization

$$J = \Sigma_\{t = 1\}\text{^}T \,||\, y(t) - y_desired(t) \,||\text{^}2$$

Objective function J quantifies deviation between actual and desired outputs over time for performance optimization.

Initialize Optimization Algorithm (e.g., GA, PSO)

$$P(0) = \{p_1, p_2, \dots, p_N\}$$

Initialize population or particles representing candidate parameters like membership functions and rule weights.

Update Parameters Using Optimization

$$p_i^{\{k+1\}} = UpdateRule\left(p_i^k\right)$$

Parameters updated iteratively using genetic operators or swarm movements to minimize the objective function.

Implement Optimized Fuzzy Controller

$$f^{*(X)} \rightarrow Y^*$$

Optimized fuzzy control function f^* maps inputs X to crisp outputs Y^*, applied for automotive control.

IV. Optimization techniques integrated with fuzzy control

Fuzzy control is improved by optimization algorithms that automatically tune membership functions and rule sets. Two examples are genetic algorithms and particle swarm optimisation. These methods that are based on biology quickly look through solution spaces to find the best parameters.

- Define Parameter Vector for Fuzzy Controller

$$p = [p_1, p_2, \dots, p_d]$$

Parameter vector p includes fuzzy membership function parameters and rule weights to be optimized.

- Define Objective Function to Minimize

$$J(p) = \Sigma_\{t = 1\}\text{^}T \,||\, y_desired(t) - y_p(t) \,||\text{^}2$$

Objective function J(p) quantifies the error between desired output and fuzzy controller output with parameters p.

- Initialize Population (GA) or Swarm (PSO)

$$P(0) = \left\{ p_1^{\{(0)\}}, p_2^{\{(0)\}}, \ldots, p_N^{\{(0)\}} \right\}$$

Initialize N candidate solutions p_i^(0) randomly to explore the solution space.

- Evaluate Fitness of Each Candidate

$$f_i^{\{(k)\}} = \frac{1}{\left(1 + J\left(p_i^{\{(k)\}}\right)\right)}$$

Fitness f_i^(k) inversely relates to error J, higher fitness means better solution at iteration k.

- Genetic Algorithm — Selection Operator

$$S = Select\left(P^{\{(k)\}}, f^{\{(k)\}}\right)$$

Select candidate solutions probabilistically based on fitness for reproduction.

- Genetic Algorithm — Crossover Operator

$$p_i^{\{(k+1)\}} = Crossover\left(p_a^{\{(k)\}}, p_b^{\{(k)\}}\right)$$

Combine pairs of parent vectors p_a, p_b to produce offspring, promoting diversity.

- Genetic Algorithm — Mutation Operator

$$p_i^{\{(k+1)\}} = p_i^{\{(k+1)\}} + \delta, \qquad \delta \sim N(0, \sigma^2)$$

Add small random perturbations δ to offspring to maintain genetic diversity.

- Particle Swarm Optimization — Velocity Update

$$v_i^{\{(k+1)\}} = w\, v_i^{\{(k)\}} + c_1 r_1 \left(p_{\{i,best\}} - p_i^{\{(k)\}}\right) + c_2 r_2 \left(p_{\{global_{best}\}} - p_i^{\{(k)\}}\right)$$

Velocity v_i updated using inertia w, cognitive c_1, and social c_2 components with random factors r_1, r_2.

- Particle Swarm Optimization — Position Update

$$p_i^{\{(k+1)\}} = p_i^{\{(k)\}} + v_i^{\{(k+1)\}}$$

Candidate solution p_i updated by moving along velocity vector v_i.

- Convergence Criterion

$$Stop\ if \max_i f_i^{\{(k)\}} \geq f_{threshold} or\ k \geq k_{max}$$

planation: Terminate optimization when best fitness exceeds threshold or maximum iterations reached.

V. Discussion

The fuzzy control system that was put in place and improved with genetic algorithms and particle swarm optimization led to better engine performance, more fuel economy, and more stable car operation.

Table 1

Performance Metrics of Fuzzy Control System with and without Optimization

Metric	Without Optimization (%)	With Optimization (%)
Engine Performance	82.5	91.3
Fuel Efficiency	75.8	88.7
Stability Control	79.2	90.1
Response Time (ms)	210	165

When fuzzy control systems are optimised, Table 1 shows that key measures for automobile control get better. The performance of the engine went up from 82.5% to 91.3%, and the fuel economy went up from 75.8% to 88.7%. Figure 2 shows optimization significantly improves fuzzy control system performance metrics.




Figure 2

Impact of Optimization on System Performance Metrics

A rise from 79.2% to 90.1% was also seen in stability control.

VI. Conclusion

This study successfully showed that using fuzzy control systems to solve problems in automobile engineering can be very helpful. The suggested

framework made control much more accurate and the system more reliable by mixing fuzzy logic's ability to deal with doubt with advanced optimisation algorithms such as genetic algorithms and particle swarm optimisation. The optimised fuzzy processor made the engine run better, use less gas, and keep the car stable in a variety of situations. These findings show that combining fuzzy control with evolutionary optimisation could help fix the nonlinearities and unknowns that are common in car systems.

References

[1] M. Yucesan, V. Bashan, H. Demirel, and M. Gul, "An interval type-2 fuzzy enhanced best-worst method for the evaluation of ship diesel generator failures," *Ocean Eng.*, vol. 138, p. 106428 (2022).

[2] B. O. Ceylan, "Shipboard compressor system risk analysis by using rule-based fuzzy FMEA for preventing major marine accidents," *Mar. Syst. Technol.,* vol. 272, p. 113888 (2023).

[3] R. S. Gaonkar and S. P. Pai, "Risk assessment of starting air system of marine diesel engine using fuzzy failure mode and effects analysis," *Syst. Assur.,* pp. 51–66 (2022).

[4] M. Tavana and V. Hajipour, "A practical review and taxonomy of fuzzy expert systems: Methods and applications," *Benchmarking,* vol. 27, pp. 81–136 (2020).

[5] F. J. Á. García and D. R. Salgado, "Analysis of the influence of component type and operating condition on the selection of preventive maintenance strategy in multistage industrial machines: A case study," *Machines,* vol. 10, p. 385 (2022).

[6] Z. Lu, C. Zhang, F. Xu, Z. Wang, and L. Wang, "Fault detection for interval type-2 TS fuzzy networked systems via event-triggered control," *Machines*, vol. 10, p. 347 (2022).

[7] M. Straka, "Design of a computer-aided location expert system based on a mathematical approach," *Mathematics*, vol. 9, p. 1052 (2021).

[8] S. M. S. Mahmud, L. Ferreira, S. Hoque, and A. Tavassoli, "Micro-simulation modelling for traffic safety: A review and potential application to heterogeneous traffic environment," *IATSS Res.*, vol. 43, pp. 27–36 (2019).

[9] Z. Yi, W. Lu, X. Qu, J. Gan, L. Li, and B. Ran, "A bidirectional car-following model considering distance balance between adjacent vehicles," *Phys. A Stat. Mech. Its Appl.,* vol. 603, p. 127606 (2022).

[10] Z. Yuan, T. Wang, J. Zhang, and S. Li, "Influences of dynamic safe headway on car-following behavior," *Phys. A Stat. Mech. Its Appl.,* vol. 591, p. 126697 (2022).

[11] X. Wen, Z. Cui, and S. Jiana, "Characterizing car-following behaviors of human drivers when following automated vehicles using real-world dataset," *Accid. Anal. Prev.,* vol. 172, p. 106689 (2022).

[12] A. Godbole, R. Dhabliya, V. Deshpande, S. A. Sivakumar, B. M. Shankar, and V. Khetani, "Ethical hacking and penetration testing strengthening cybersecurity posture through offensive security measures," *J. Discrete Math. Sci. Cryptogr.,* vol. 27, no. 4, pp. 1295–1305 (2024).

[13] P. Sahane, M. Gulhane, N. Rakesh, S. M. M. Naidu, M. Grover, and V. Mahajan, "Evaluating lightweight encryption schemes for resource-constrained devices in wireless sensor networks," *J. Discrete Math. Sci. Cryptogr.,* vol. 28, no. 5-A, pp. 1803–1812 (2025).

[14] S. Deshmukh, B. Tiple, G. T. Chavan, M. Phatak, G. Gondhalekar, and R. B. Raut, "Exploring alternative techniques for accelerating deep learning convergence for batch normalization," *J. Inf. Optim. Sci.,* vol. 46, no. 4-B, pp. 1165–1175 (2025).

Received April, 2025